

# Variomax V

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

## Product description

- Easy-to-use, automatically engaging aluminium safety hinge.
- Safe height adjustment thanks to four pull handles of diecast aluminium.
- Single ladder, stepladder and stair ladder in one.
- Rung by rung height adjustment in increments of 280 mm.
- Quickly and easily converts from one mode to another.
- High strength, non-twist rung/stile connections.



to the product



## Product features

Coating: natural  
 Connection between stiles and rungs/stiles: flanged  
 Load: max. 150 kg  
 Material: aluminium  
 Product type: Flanged telescopic multipurpose ladder, 4 sections  
 Tread depth: 30 mm  
 Type of rungs/treads: serrated  
 Vertical distance between each rung/tread: 265 mm



## Hints and special features

Does not comply with EN131-1+2.

## Product variants

Order number	Dimensions, folded	Length	Length as lean-to ladder	Length as trestle	Number of rungs	Number of rungs	Transport dimensions	Weight	Width	Working height as lean-to ladder	Working height as stepladder
41934	0,97 m × 0,5 m × 0,21 m	0.97 m	2.97 m	1.45 m	3	4 × 3	970 mm × 500 mm × 210 mm	9 kg	0.5 m	3.85 m	2.75 m
41930	1,3 m × 0,56 m × 0,21 m	1.3 m	4.2 m		4	4 × 4	1.310 mm × 560 mm × 210 mm	13 kg	0.56 m	5 m	3.35 m
41383	1,3 m × 0,64 m × 0,21 m	1.3 m	4.2 m	2 m	4	4 × 4	1.310 mm × approx. 640 mm × 210 mm	15 kg	0.64 m	5 m	3.35 m
41931	1,58 m × 0,63 m × 0,21 m	1.58 m	5.3 m		5	4 × 5	1.580 mm × 630 mm × 210 mm	16 kg	0.63 m	6.05 m	3.85 m
41384	1,58 m × 0,71 m × 0,21 m	1.58 m	5.3 m	2.54 m	5	4 × 5	1.580 mm × approx. 710 mm × 210 mm	18 kg	0.71 m	6.05 m	3.85 m
41932	1,86 m × 0,7 m × 0,21 m	1.86 m	6.4 m		6	4 × 6	1.860 mm × 700 mm × 210 mm	20 kg	0.7 m	7.1 m	4.4 m
41385	1,86 m × 0,78 m × 0,21 m	1.86 m	6.4 m	3.1 m	6	4 × 6	1.860 mm × approx. 780 mm × 210 mm	22 kg	0.78 m	7.1 m	4.4 m