

# POOL=CARE

BY DANNER MANUFACTURING

## POOL MAIN DRAIN UTILITY PUMP

**POOL-CARE MAIN DRAIN UTILITY PUMP** is a powerful and durable utility pump that is designed primarily for draining in-ground swimming pools. The slotted "basket" base measures less than 5 1/2-inches in diameter, which allows the pump to fit inside any standard 8" main drain and seat itself several inches below the top surface of the pool's main drain flange. With a maximum flow rate of 5373 GPH, it can quickly and efficiently remove water from any in-ground Swimming Pool.

### MAIN DRAIN PUMP FEATURES:

- Maximum Flow Rate: 5373 GPH or 90 GPM
- Maximum Head Height: 32-feet
- Pumps Down to 1 1/2" to 2" water depth (1 1/2" with feet removed from base)
- Fits in standard 8" Pool Main Drain Allowing for Complete Drainage
- Includes 1 1/2" Threaded Barbed Fitting
- Removable Elbow for Vertical or Horizontal Discharge Options
- Integrated Carry Handle
- 25' Cord with Flexible Strain Relief
- Completely Submersible
- Slotted Base Constructed from High Impact Polypropylene
- 316 Marine Grade Stainless Steel Hardware
- Optional Tethered Float Switch for Automatic Shut-Off
- Packed 2 per Master Carton
- 1 Year Limited Warranty\*



Main Drain Pump Shown with Optional Tethered Float Switch for Automatic Shut-Off

### TETHERED FLOAT SWITCH FEATURES:

- Mechanically-Activated Snap Action Contacts
- Corrosion Resistant High Impact Polypropylene Float Housing

### MAIN DRAIN PUMP - ITEM# 20370

Max. Flow Rate	5373 GPH
Max. Pumping Height	32'
Max. Watts/Amps	593/4.9
Weight	12 lbs.
Dimensions w/ Elbow (W x H)	9 3/4" x 15 1/2"
Dimensions w/out Elbow (W x H)	7 1/4" x 15 1/2"

### TETHERED FLOAT SWITCH - ITEM# 20375

Cord Length: 30' with Piggy Back Plug



A Proud American Manufacturer

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

©2018 Danner Mfg. Inc. All rights reserved. Islandia, New York 11749-1489 | www.dannermfg.com

\*1 Year Limited Warranty does not include external attachments.