
## **GCWM1069**


## LG PLATINUM ON-PREMISE LAUNDRY WASHER

## **PRODUCT SPECS**

CYLINDER	
Capacity Ibs	22.5
Cylinder Diameter <i>inch</i>	22.1
Cylinder Depth <i>inch</i>	16.5
,	3.6
Cylinder Volume <i>cu ft</i>	3.0
DIMENSIONS & WEIGHT	101.0
Net Weight <i>lbs</i>	191.8
Crated Weight Ibs	211.6
Machine Dimensions <i>inch</i> WxDxH	27 x 29.8 x 38.7
Machine Depth w/Door Opening inch	50.8
Shipping Dimensions <i>inch</i> WxDxH	29.7 x 31.3 x 44.4
SPEED	
Washing Speed <i>rpm</i>	50
Extract (High Speed) rpm	1150
G-force	413
WATER USAGE	
Water Consumption gal	13.4
NOISE & CYCLE TIME	
Noise Level (sound power) dB	< 62
Program Duration (default) mins	36
SYSTEM & CONTROL	
Inverter Direct Drive Motor	•
Intelligent Electronic Controls	•
3 Compartment Dispenser	•
Forced Drain System	•
ETERNAL FINISH	
Drum	Stainless Steel Drum
Top Plate	Porcelain (Single) / Painted Steel (Stack)
Transparent Glass Window Door	•
Colors	Platinum
Cabinet	Painted Steel
Control Panel	Painted Steel
CONNECTIONS	
Available Voltages <i>V/Hz/Ph</i>	120/60/1
PCB Fuse - Main Control Board Amps	12
PCB Fuse - Filter Assembly <i>Amps</i>	15
HOSE	
Inlet Hose ft	4.92
Drain Hose ft	6.56
ENERGY SAVINGS INFORMATION	
Modified Energy Factor <i>MEF</i> *	2.6
Water Consumption Factor <i>WCF*</i>	3.7
	gation. Contact Girbau North America at (800) 256-1073

Specifications subject to change without notice or obligation. Contact Girbau North America at (800) 256-1073 for dimensions not shown or for clarification.





Front View

29.8" — | (756 mm) 4" (100 mm)

Side View





Nodified Energy Factor (MEF) measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) measured in gallons per cycle per cylinder cubic feet. MEF and WCF statistics are according to Department of Energy (DOE) testing standards report by LG Commercial Laundry.