
TCW2013


LG TITAN PRO ON-PREMISE LAUNDRY WASHER


PRODUCT SPECS

CYLINDER	
Capacity Ibs	35
Cylinder Diameter inch	24
Cylinder Depth inch	20.4
Cylinder Volume cu ft	5.2
DIMENSIONS & WEIGHT	
Net Weight Ibs	221.8
Crated Weight <i>lbs</i>	248
Machine Dimensions <i>inch</i> WxDxH	29 x 32 x 40.8
Machine Depth w/Door Opening inch	53
Shipping Dimensions <i>inch</i> WxDxH	31 x 33.3 x 44.3
SPEED	
Washing Speed rpm	46
Extract (High Speed) rpm	980
G-force	327
WATER USAGE & CONNECTIONS	
Water Inlets inch	2 @ 3/4
Drain Diameter inch	2
Water Consumption gal	17.8
NOISE & CYCLE TIME	
Noise Level (sound power) dB	< 62
Program Duration (default) mins	35
SYSTEM & CONTROL	
Inverter Direct Drive Motor	•
Intelligent Electronic Controls	•
3 Compartment Dispenser	•
Forced Drain System	•
ETERNAL FINISH	
Drum	Stainless Steel Drum
Top Plate	Painted Steel
Transparent Glass Window Door	•
Colors	Platinum
Cabinet	Painted Steel
Control Panel	Painted Steel
CONNECTIONS	
Available Voltages <i>V/Hz/Ph</i>	120/60/1
PCB Fuse - Main Control Board <i>Amps</i>	12
PCB Fuse - Filter Assembly <i>Amps</i>	15
HOSE	
Inlet Hose ft	4.92
Drain Hose ft	6.82
ENERGY SAVINGS INFORMATION	
Modified Energy Factor MCC*	2.4
Modified Energy Factor <i>MEF*</i>	









Specifications subject to change without notice or obligation. Contact Girbau North America at (800) 256-1073 for dimensions not shown or for clarification.

*Modified Energy Factor (MEF) measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) measured in gallons per cycle per cylinder cubic feet. MEF and WCF statistics are according to Department of Energy (DOE) testing standards report by LG Commercial Laundry.



