Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

## Section 1. Identification of the substance or the mixture and of the supplier

#### 1.1 Product Identifier

Product identifier: Frothing Lager `SLC0691(Contains:Benzyl benzoate, Isoeugenyl methyl ether, Linalool,

Phenethyl acetate)

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

**Product uses:** Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Scent Method

Company address: 237 Kurrajong Road

**Prestons** NSW 2170 Australia

**Contact:** Regulatory Affairs

E-Mail address: ravi@scentmethod.com

Company phone: 0419 142 507 1.4 Emergency telephone number 0419 142 507 **Emergency phone:** 

## Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

Class and category of Acute Toxicity - Oral Category 5 danger:

Skin Corrosion / Irritation Category 3

Eye Damage / Irritation Category 1 Sensitization - Skin Category 1

Hazardous to the Aquatic Environment - Acute Hazard Category 1 Hazardous to the Aquatic Environment - Long-term Hazard Category 2

H303, May be harmful if swallowed.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage. H316, Causes mild skin irritation. H400, Very toxic to aquatic life.

H411, Toxic to aquatic life with long lasting effects.

## 2.2 Label elements

Signal word: Danger

Hazard statements: H303, May be harmful if swallowed.

H317, May cause an allergic skin reaction.

Scent Method, 237 Kurrajong Road, Prestons, NSW, 2170, Australia

Issue date: 30/05/2023 Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

H318, Causes serious eye damage. H316, Causes mild skin irritation. H400, Very toxic to aquatic life.

H411, Toxic to aquatic life with long lasting effects.

Precautionary statements:

P261, Avoid breathing vapour or dust.

P272, Contaminated work clothing should not be allowed out of the workplace.

P273, Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection. P302/352, IF ON SKIN: Wash with plenty of soap and water.

P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310, Immediately call a POISON CENTER or doctor/physician.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P363, Wash contaminated clothing before reuse.

P391, Collect spillage.

P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.



Pictograms:

2.3 Other hazards

Other hazards: None

### Section 3. Composition / information on ingredients

#### 3.2 Mixtures

#### Contains:

Name	CAS	%	GHS Classification
Benzyl benzoate	120-51-4	20-<50%	Acute Tox. 4-Acute Tox. 5-Aquatic Acute 1-Aquatic Chronic 2;H302-H313-H400-H411
Benzyl alcohol	100-51-6		Acute Tox. 4-Acute Tox. 5-Eye Irrit. 2A;H302-H313-H319
Phenethyl alcohol	60-12-8	10-<20%	Acute Tox. 4-Acute Tox. 5-Skin Irrit. 3-Eye Irrit. 2A; H302-H313-H316-H319
Phenethyl acetate	103-45-7	5-<10%	Acute Tox. 5-Eye Dam. 1-Aquatic Acute 3;H303-H318- H402
Ethyl maltol	4940-11-8	5-<10%	Acute Tox. 4-Aquatic Acute 2;H302-H401
Ethyl octanoate	106-32-1	1-<5%	Flam. Liq. 4-Aquatic Acute 2-Aquatic Chronic 2;H227- H411
Benzyl formate	104-57-4	1-<5%	Flam. Liq. 4-Acute Tox. 4-Acute Tox. 5-Skin Irrit. 2; H302-H227-H315-H313

Issue date: 30/05/2023 Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

Phenethyl formate	104-62-1	1-<5%	Acute Tox. 5-Skin Irrit. 3;H303-H316
Ethyl nonanoate	123-29-5	1-<5%	Flam. Liq. 4-Skin Irrit. 3;H227-H316
Ethylene brassylate	105-95-3	1-<5%	Aquatic Acute 2;H401
Isoeugenyl methyl ether	93-16-3	1-<5%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 3;H303-H317-H402
Linalool	78-70-6	1-<5%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3;H227-H303-H315-H317-H319-H402
Linalool oxide	1365-19-1	0.1-<1%	Flam. Liq. 4-Acute Tox. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A;H302-H227-H315-H313-H319

### Substances with workplace exposure limits, not listed above:

Not Applicable

#### Section 4. First-aid measures

#### 4.1 Description of first aid measures

**Inhalation:** Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

**Skin exposure:** IF ON SKIN: Wash with plenty of soap and water.

**Ingestion:** Rinse mouth with water and obtain medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

May be harmful if swallowed.

May cause an allergic skin reaction.

Causes serious eye damage.

Causes mild skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

## **Section 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

## 5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

### 5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Version: 2 (30/05/2023)

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

#### Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

#### 6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

## 6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

#### 6.4 Reference to other sections:

Also refer to sections 8 and 13.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

# 7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

## 7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

#### Section 8. Exposure controls/personal protection

## 8.1 Control parameters

Workplace exposure limits: Not Applicable

#### **8.2 Exposure Controls**

#### **Eye / Skin Protection**

Wear protective gloves/eye protection/face protection

## **Respiratory Protection**

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Issue date: 30/05/2023 Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

## Section 9. Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Appearance:

Odour:

Not determined

Odour threshold:

Not determined

Evaporation rate: Not determined Flammability (solid, gas): Not determined

Upper/lower flammability or explosive limits: Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Not determined Relative density: Not determined Solubility(ies): Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined **Decomposition temperature:** Not determined Viscosity: Not determined **Explosive properties:** Not expected **Oxidising properties:** Not expected

**9.2 Other information:**None available

#### Section 10. Stability and reactivity

## 10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

### 10.2 Chemical stability:

Good stability under normal storage conditions.

### 10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

#### 10.4 Conditions to avoid:

Avoid extreme heat.

### 10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

## 10.6 Hazardous decomposition products:

Not expected.

## Section 11. Toxicological information

## 11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity: Acute Toxicity - Oral Category 5

Acute Toxicity Oral 2008
Acute Toxicity Dermal >5000

Acute Toxicity Inhalation Not Available

Skin corrosion/irritation:Skin Corrosion / Irritation Category 3Serious eye damage/irritation:Eye Damage / Irritation Category 1Respiratory or skin sensitisation:Sensitization - Skin Category 1

Germ cell mutagenicity:

Based on available data the classification criteria are not met.

Carcinogenicity:

Based on available data the classification criteria are not met.

Reproductive toxicity:

Based on available data the classification criteria are not met.

STOT-single exposure:

Based on available data the classification criteria are not met.

STOT-repeated exposure:

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

## Information about hazardous ingredients in the mixture

Ingredient	CAS	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
Benzyl alcohol	100-51-6	1620	2500	Not available	Not available
Benzyl benzoate	120-51-4	1500	4000	Not available	Not available
Benzyl formate	104-57-4	1000	2180	Not available	Not available
Ethyl maltol	4940-11-8	1200	Not available	Not available	Not available
Isoeugenyl methyl ether	93-16-3	2500	Not available	Not available	Not available
Linalool	78-70-6	2790	Not available	Not available	Not available
Phenethyl acetate	103-45-7	2500	Not available	Not available	Not available
Phenethyl alcohol	60-12-8	1610	2500	Not available	Not available
Phenethyl formate	104-62-1	3220	Not available	Not available	Not available

Refer to Sections 2 and 3 for additional information.

#### **Section 12. Ecological information**

# 12.1 Toxicity:

Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability:** Not available

**12.3 Bioaccumulative potential:** Not available

**12.4 Mobility in soil:** Not available

**12.5 Other adverse effects:** Not available

### **Section 13. Disposal considerations**

#### 13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## **Section 14. Transport information**

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, Ethyl octanoate)	9	-	III
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, Ethyl octanoate) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, Ethyl octanoate)	9	-	III
ICAO TI	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, Ethyl octanoate)	9	-	III

**14.5 Environmental hazards:** This is classified as an environmentally hazardous substance under the UN

Model Regulations. This is classified as a Marine Pollutant under the IMDG

Code.

**14.6 Special precautions for user:** None additional

## 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

# Section 15. Regulatory information

None additional

Version: 2 (30/05/2023)

## **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

### **Section 16. Other information**

**Concentration % Limits:** EH A1=80.65% EH A2=7.77% EH A3=0.77465574% EH C2=70.88% EH

C3=7.09% EH C4=70.88% SCI 3=19.79% EDI 1=38.22% EDI 2A=9.23%

SS 1=62.11%

**Total Fractional Values:** EH A1=1.24 EH A2=12.86 EH A3=129.09 EH C2=1.41 EH C3=14.11 EH

C4=1.41 SCI 3=5.05 EDI 1=2.62 EDI 2A=10.84 SS 1=1.61

## Key to revisions:

2.1 Classification of the substance or mixture

SECTION 3: Composition/information on ingredients

## Key to abbreviations:

Abbreviation	Meaning	
Acute Tox. 4	Acute Toxicity - Oral Category 4	
Acute Tox. 5	Acute Toxicity - Dermal Category 5	
Acute Tox. 5	Acute Toxicity - Oral Category 5	
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1	
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2	
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3	
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2	
Eye Dam. 1	Eye Damage / Irritation Category 1	
Eye Irrit. 2A	Eye Damage / Irritation Category 2A	
Flam. Liq. 4	Flammable Liquid, Hazard Category 4	
H227	Combustible liquid.	
H302	Harmful if swallowed.	
H303	May be harmful if swallowed.	
H313	May be harmful in contact with skin.	
H315	Causes skin irritation.	
H316	Causes mild skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	
H401	Toxic to aquatic life.	
H402	Harmful to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.	
P261	Avoid breathing vapour or dust.	
P264	Wash hands and other contacted skin thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/eye protection/face protection.	

Version: 2 (30/05/2023)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

**Product:** Frothing Lager `SLC0691

Version: 2

P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.