

BREMA CB316A

SELF-CONTAINED ICE CUBE MACHINE

Brema's flagship CB range offers selfcontained ice machines for bench top, under bench or free-standing installation. These machines produce attractive, crystalline cubes weighing 13g which rapidly chill and enhance the appearance of any beverage.


The Brema CB316A is an under bench ice cube machine that produces 33kg of ice per 24 hours and has storage capacity of 16kg.

The CB range of self-contained ice cube machines is the perfect fit for cafes, restaurants, hotels, bars and nightclubs.



STANDARD FEATURES

- 33kg production per 24 hours
- 16kg storage capacity
- Produces crystalline 13g cubes
- Production rated at 21°C air and 15°C water
- Hospital grade stainless steel outer
- Fully insulated internal storage bin
- Disappearing door
- Electromechanical operation
- Stainless steel spray arm



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695 96-100 Tope Street

South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 3 8699 1299

Sydney

20/4 Avenue of the Americas Newington, NSW 2127

Tel: +61 2 9748 3000 Fax: +61 2 9648 4762 Brisbane


1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Unit 4/35 Westchester Road Malaga WA 6090 +61 8 9248 9290 Tel: Fax: +61 8 9248 1903



BREMA CB316A





DIMENSIONS

500W x 580D x 690*H mm (*add 110-150mm for adjustable legs)

CONNECTIONS

3/4" Water inlet, 24mm Water outlet & Electical connection

STANDARD ACCESSORIES

- Water inlet hose
- Drainage hose
- External water filter
- Pressure limiting valve
- Plastic ice scoop
- Adjustable stainless steel legs (4)

TECHNICAL DATA

Production 24h	33 kg
Storage Capacity	16 kg
Cooling System	Air
Cube	13 g
Refrigerant	R404A
Electrical Consumption	370W
Power Requirements	240V 10amp
Weight	48 kg

CONNECTIONS	W	Н
Water inlet	111 mm	196 mm
Water outlet	49 mm	151 mm
Electrical connection	156 mm	232 mm
Clearances	Rear: 100 mm	Sides: 100 mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



PROUDLY DISTRIBUTED BY:

