## PRODUCT SPECIFICATION SHEET

## Sensory Wall Cascade





The Sensory Wall Cascade offers a unique sensory experience which will captivate the mind and provide a soothing effect for many children and adults.

Unlike similar products, the UFO Sensory Wall Cascade has an inbuilt remote control LED illuminator with full color change. this avoids the need for bulky and hot external units. We have also incorporated a unique cantilever mounting bracket, allowing for secure fixing and much more freedom in the positioning of the Cascade. Our Cascade system can easily be installed on walls, or above doors, and swung out ready for use. No other system offers so much flexibility.

The PMMA fiber used in this product has CPSIA and EN71 toy certifications. this means you can be sure you are buying a safe, rigorously tested product.

CASCADE SPECIFICATIONS	
Fiber Type	2.2mm diameter PMMA side sparkle
No. of Fiber Tails	SWC10: 90, all at 2 meter (6.56ft) length SWC12: 108, all at 2 meter (6.56ft) length
Operating Environment	Indoor / dry
Material	Aluminum
Finish	White powdercoat
Dimensions	52mm diameter at either 1000 or 1200mm long (2.05") diameter at either 3.28ft or 3.94ft long)

ELECTRICAL SPECIFICATIONS	
Supply Voltage	110-240V AC 50/60 Hz
Power Supply	External 12V PSU
Power Consumption	2-5W in color cycle mode

## **DRIVER BOX SPECIFICATIONS**

FLECTDICAL CDECIFICATIONS

Material	ABS
Finish	White
Dimensions (LxWxH)	137mm x 114mm x 73mm (5.39" x 4.49" x 2.87")
Cable Length	2 meter (6.56ft) cable to cascade





