

ESLPD3S100 | BATH Ventilation



Ventilation Fan

Remove odours and humidity quietly and efficiently with our Energy STAR certified high-performance bath fan. Equipped with a high-density polyethylene (hard rigid plastic) fan for ultra-quiet operation and long-lasting durability. Choose your fan speed for optimum CFM output. Incredibly low-profile bath fan makes installation and accommodation a breeze. Our ceiling-mounted fan meets all cETLus safety standards.



Customize with the following SMART Options:

- **Humidity Sensor** to automatically regulate moisture and protect your home and family from mold
- **Motion Sensor** for unparalleled convenience

Features

- 3 speed options in one fan: 50 CFM / 80 CFM / 100 CFM
- Max. 1.2 sones
- Thermal fuse protection
- Energy Star approved
- Includes 4" duct connector
- Recommended for bathrooms up to 95 sqft (8' ceiling)
- Low speed runs continuously (Adjustable 0, 30 CFM to Max. CFM)

Housing

- Wiring from inside or outside housing with 8" leads
- 26 gauge galvanized steel housing (corrosion resistant)

Motor

- Includes a built in overload disconnect for safety and longer motor life
- Includes a capacitor start motor that performs with high efficiency and long lasting reliability
- Plug-in permanently lubricated DC motor, engineered for continuous operation

Installation

- Fit any joist from Min: 12" to Max: 24" width spans
- Can be mounted with flange or hanger bars
- 4" diameter duct connectors supplied
- Heavy duty triple point mounting brackets that can be adjusted up to 24 inch joist centers without vibration
- Premium grille is made of rugged polymeric resin for durability & comes with torsion spring clips for even mounting



Cyclone Range Hoods Inc.

1361 Huntingwood Drive, Unit 16. Toronto, ON. M1S 3J1. Canada.


Toll Free: 1-888-293-5662

Tel: (416) 293-0933

Fax: (416) 293-4793



Website: www.CycloneRangeHoods.com

ESLPD3S100 | BATH Ventilation



SPECIFICATIONS		ESLPD3S100		
Static Pressure		0.1	0.1	0.1
Noise Level (Sones)		0.6	1.0	1.2
Air Flow Volume (CFM)		50	80	100
Current (Amps)		0.1		
Power Consumption (Watts)		12		
Electrical Connection (V/Hz)		120/60		
Thermal Fuse Protection		Yes		
Motor Type		DC		
Blower Wheel		Centrifugal		
Duct Diameter		4"		
Humidity Sensor		*		
Motion Sensor		*		

*Available Smart Options



Model	Description	Packaging	Contractor Pack	Master Pack
ESLPD3S100	Bathroom Ventilation	Individual	-	-
ESLPD3S100H	with Humidity Sensor	Individual	-	-
ESLPD3S100M	with Motion Sensor	Individual	-	-
ESLPD3S100MH	with Motion and Humidity Sensor	Individual	-	-