



HIGH PERFORMANCE tape for PUNCTURE-FREE mounting of sheet membranes to structural substrates.

Twinet is a strip of pressure-sensitive, acrylic adhesive reinforced with an embedded fiber-strand carrier layer and a tear-proof plastic backing.

Use Twinet as a mounting aid for vapor control layers (VCL) to hard surface framing members and panel goods. Eliminates leakage points common to mechanical fasteners. Optimal for use with metal studs, where hand-staples are ineffective. Not for permanent structural mounting.

CHARACTERISTICS

ROLL DIMENSIONS	¾" x 164 ft
THICKNESS	14 mils
MINIMUM RECOMMENDED INSTALLATION TEMPERATURE	14°F (-10°C)

- ✓ Extremely adhesive on both sides
- ✓ Protective coating on each roll face, prevents adhesion of jobsite debris
- ✓ Plastic backing is tear-proof, even in tight spaces



INSTALLATION INSTRUCTIONS



- Apply strip of Twinet to each framing member
- Remove backing strip



- Install vapor control layer per manufacturer's instructions
- Press firmly onto Twinet



- Permanently maintain vapor control layer with mechanical methods, such as battens or interior finish

All SIGA products are backed by a 10 year limited warranty. Reference siga.swiss for complete details. We want you to maximize the performance potential of Twinet on your project. Contact one of our Application Advisors for assistance, from architectural details to jobsite training.