

## Beewax Premium

Version: apr-21

*Beewax Premium* is a natural wax for the protection of lime-based venetian stuccos and plasters. It prevents the absorption of water and its pollutants without altering the permeability of the substrate to gases or water vapor. In addition, it prevents the depigmentation of intense colours.

### PRODUCT DESCRIPTION

#### Features:

Protection of lime-based Venetian stuccos..  
Does not alter substrate breathability.  
Prevents depigmentation of intense colours.  
Excellent workability.  
High resistance and durability.  
Natural wax base.  
Suitable for interiors and exteriors.

#### Technical properties:

Specific weight	0.9 ± 0.05 g/cm <sup>3</sup>
pH	9.5 ± 1
Composition	Wax
Appearance	Yellowish liquid
Finish	Transparent

#### Yield/Coverage:

Between 30-40 m<sup>2</sup>/L or 1220-1630 Sq.Feet per Gallon (1 coat). However, exact yield depends on type and condition of substrate, as well as tools used. Exact consumption should be determined by making onsite sample.

#### Pack Size:

0.75L, 1Gal and 4L.

#### Storage:

Store in original container. Keep tightly sealed in cool, dry place. Do not store in extremes of temperature, avoid direct exposure to sunlight and protect from frost. Unopened, storage stability is 36 months from date of manufacture.

### APPLICATION METHOD

#### Substrate Types:

Lime Venetian stucco or plaster.

#### Substrate Condition:

The substrate must be dry, firm, well adhered, even and free of any impurities that could hinder the perfect bonding of the product.

#### Application method:

Apply 1 or 2 coats according to absorption of the substrate and application location i.e. interior / exterior. Spread the product adequately. After 30-60 minutes from initial application, polish with a wool mop. If the mop becomes coated in wax, allow more drying time before polishing.

#### Drying:

At 25 °C (77 °F) and 60% relative humidity: 24 hours per coat.

#### Ambient conditions:

The working temperature (ambient and substrate) must be between +5 °C and +32 °C (41 °F and 90 °F). Do not apply under direct sunlight, on surfaces heated by the sun, or in anticipation of rain.

#### Tools:

Sponge, trowel or short-haired glove. Wool mop (polished).

#### Tool cleaning:

Clean tools after use with warm water.

## Notes:

Do not apply to surfaces in permanent contact with water. It is not a waterproofing system.

In case of rain, let the surface dry at least 24 hours before application.

It is recommended to protect the treated surface from rain and atmospheric humidity for 4 days.

For decorative glazing and/or the application of self-adhesive templates or other types of masking, please allow 1 week to elapse.

Should there be any strict aesthetic requirements, it is recommended to carry out preliminary tests.

Parts that are not going to be treated should be protected (glassware or carpentry).

To maintain product efficacy do not mix with other brands.

## ADDITIONAL INFORMATION

### Usage warnings:

None, particularly in situations where normal product application is expected and by people without any specific medical conditions. Alkaline product, protect skin and eyes especially. Do not inhale the product. Keep out of reach of children.

### Waste management:

According to local legal regulations. The containers are made of polypropylene. Please contribute to the protection of the environment, do not throw waste down the drain and use the nearest recycling point.

## Sustainability gesture:

Minimise product waste by carefully estimating the amount you will need. Store any unused product for future use according to the "Storage" guidelines.

## Safety information:

For information regarding safety, physical, ecological and toxicological details please see the latest version of the product's Material Safety Data Sheet.

## Technical Support:

For further information, please contact your local distributor or manufacturer.  
([technicalsupport@graphenstone.com](mailto:technicalsupport@graphenstone.com)).

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.