

FICHA TÉCNICA
LUMINARIO LED
INDUSTRIAL STD 2.0



Especificaciones:

Modelo	HB01028F	HB01029F	HB01020F
Potencia	100 W	150 W	200 W
Temperatura de color	6 500 K		
Flujo luminoso	15 000 lm	22 500 lm	30 000 lm
Voltaje	100 V~ - 277 V~		
Frecuencia	50 Hz / 60 Hz		
Corriente	1.00 A - 0.36 A	1.50 A - 0.54 A	2.00 A - 0.72 A
Dimensiones (A x B)	Ø 231 x 84 mm	Ø 282 x 89 mm	Ø 325 x 92 mm
Color	Negro		
Material	Aluminio / PC		
Consumo	0.10 kWh	0.15 kWh	0.20 kWh
Factor de Potencia	>0.90		

* Referir su consulta al marcado o etiquetado del luminario.



THD < 20%



IK 08



Surge Protection
6 KV

LED NOM

Boomer[®]
 Lighting
 LA LUZ DE TU VIDA

IP 65

☀ Exterior

✓ 50 000 h

∠ 130°

Dimensiones (A x B)

GARANTÍA
5 AÑOS
 LED
 BOOMER LIGHTING™



f **boomer.mx**