



Art.No 29108 - 03

## Additive A34

### Description

Additive A34 is an antifoam which is used against increased foaming tendency with Blasocut or Vasco emulsions. The antifoam is free of silicone, but the product contains zero-residue polysiloxane components.

### Properties

Efficient defoamer with instant impact for use in Blasocut and Vasco emulsions. Additive A34 is free of silicone and therefore does not affect succeeding treatments of workpieces.

### When to use it

In Blasocut emulsions if after a new charge up the hardening up (formation of calcium soap) did not get effective.  
In Blasocut emulsions with extreme foaming tendency or in case hardening up did not reach its effectiveness.

In Vasco emulsions with increased foaming tendency.  
Not be used with synthetic solutions.

### How to use it

Dosage: 100–250 ml per 1'000 liters of emulsion.

#### **Shake well before using!**

Carefully dissolve in water in the ratio 1:10, then slowly add in a turbulent zone. Add after filtration process since Additive A34 may be dragged/filtered out in the beginning.

### Handling/Storage

Storage: Store in closed original container at temperature from 0°C to +40°C (41°F to 104°F).  
Do not expose to direct sunlight.

Transport: No hazardous good according to ADR

### Safety and environmental aspects

For more detailed information please consult the EC Safety Data Sheet.

Information contained in this data sheet is based upon the properties and applications of use as known to us. However, generally no legal liability may be deducted from such information.

S058 24.04.2019 V 01