



DUO-SAFETY LADDER CORPORATION



Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid.

Series 1000-A

2 3/4" Channel Rail
750 lb Duty Rated

SPECIFICATIONS

SERIES 1000-A 2-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
10'	7' 2.25"	18.5"	4.56"	29#
12'	8' 2.25"	18.5"	4.56"	32#
14'	9' 2.25"	18.5"	4.56"	34#
16'*	9' 11.5"	18.5"	4.56"	40#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

*Only the 16' length has a pulley and 3/8" manila rope installed
All other lengths are raised manually



*The end-all in fire safety**

Fire-End & Croker®

800-759-3473 | fire-end.com | info@fire-end.com

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com