



DUO-SAFETY LADDER CORPORATION

Aluminum Wall Ladders

Famous Duo-Safety Rail Construction provides the advantage of extra strength without cumbersome weight. Ideal for pumper use - these outstanding ladders have been proven and approved for many years by fire companies everywhere.

- Series 750-A**
- Series 850-A**
- Series 1250-A**

Channel Rail Construction
750 lb Duty Rated

SPECIFICATIONS

SERIES 750-A WALL

Size	Length	Width	Rail Size	Weight
8'	8' 2.25"	19"	2.75"	14#
10'	10' 2.25"	19"	2.75"	17#
12'	12' 2.25"	19"	2.75"	20#
14'	14' 2.25"	19"	2.75"	25#

SERIES 850-A WALL

Size	Length	Width	Rail Size	Weight
16'	16' 2.5"	19"	3.25"	35#
18'	18' 2.5"	19"	3.25"	43#
20'	20' 2.5"	19"	3.25"	45#

SERIES 1250-A WALL

Size	Length	Width	Rail Size	Weight
25'	25' 3"	19"	3.75"	62#
30'	30' 3"	19"	3.75"	70#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com