



XD™ WASHDOWN KIT

Simple and built to last, the XD Washdown Kit is the perfect addition needed for after-the-fire cleanup. It is ideal for cleaning up equipment, tools, dirty hose, or contaminated turnout gear. The high-quality components that make up this kit are far superior what you would find from a local hardware or big box store.

KIT INCLUDES:

- XD Washdown Nozzle built tougher than any other garden hose nozzle
- Model 104A swivel bell reducer to make attachment simple with no hose twisting
- 50' x 5/8" garden hose rated for pressures up to 300 psi (20 BAR) equipped with brass couplings
- A rugged carrying bag with durable seat belt handles and vents to aid in drying after putting away wet

HELP REMOVE CONTAMINANTS



The XD Washdown Nozzle is made of lightweight aluminum with stainless steel and brass components which includes a trigger controlled variable spray pattern that instantly shuts off when trigger is released. Built for long term use, this is not your ordinary garden hose nozzle.

- Flows 7 gpm @ 100 psi (27 LPM @ 7 BAR)
- Equipped with an insulated rubber cover with red direction arrows ready to withstand the harshest use
- Brass swivel inlet adapter included to eliminate hose twists at the nozzle
- Rated for 150 psi (10 BAR) with brass couplings



222-1.5" Wat-R-Wall Water Curtain

- 100 gpm @ 100 psi (380 LPM @ 7 BAR)
- Chrome plated brass construction
- 1.5" female free swivel inlet



222-2.5" Wat-R-Wall Water Curtain

- 100 gpm @ 100 psi (380 LPM @ 7 BAR)
- Chrome plated brass construction
- 2.5" female free swivel inlet



Model LR Cellar Nozzle

- 160 gpm @ 100 psi (600 LPM @ 7 BAR)
- 20 ft. (6 meter) spray diameter
- Chrome plated brass construction
- 1.5" female rigid inlet




Model R Cellar Nozzle

- 350 gpm @ 100 psi (1330 LPM @ 7 BAR)
- 55 ft. (16.7 m) spray diameter
- Chrome plated brass construction
- 2.5" female rigid inlet



193-6-2.5" Bresnan Distributor Nozzle

- 395 gpm @ 100 psi (1495 LPM @ 7 BAR)
- 45 ft. (13.7 m) spray diameter
- Chrome plated brass construction
- 2.5" female rigid inlet



A-1.5" Applicator

- For use with Cellar and Distributor Nozzles
- Chrome plated brass construction
- 1.5" free swivel inlet x 1.5" male outlet

A-2.5" Applicator

- For use with Cellar and Distributor Nozzles
- Lightweight aluminum construction
- Red urethane enamel finish
- 2.5" free swivel inlet x 2.5" male outlet