



Case Material/Lens: Housing made from high impact, super tough nylon offering exceptional durability. Available in international safety orange and safety yellow with rubberized cushioned-grip handle. Rotating head constructed from high grade aluminum incased in super tough nylon; Unbreakable polycarbonate lens with scratch-resistant coating. Gasket sealed.

Dimensions/Weight: 7.43 in. (18.8 cm); Width: 4.32 in. (10.9 cm); Height: 4.36 in. (11.0 cm); 2.47 lbs. (1123 grams)

Light Source: Three C4® LEDs, impervious to shock with a 50,000 hour lifetime. Two ultra bright blue taillight LEDs ensure you can be seen even from behind

Light Output/ High: 1,200 lumens; 75,000 candela; 548m beam; runs 4.75 hours

Run Time/ Low: 350 lumens; 22,000 candela; 296m beam; runs 12 hours

Three deep-dish parabolic reflectors produces a tight beam with optimum peripheral. Optimized electronics provide regulated intensity

On/Off: Large, multi-function, push-button switch on top of light is easy to use with gloves

Battery: Rechargeable 8800 mAh Lithium Ion battery. Fully recharges in 9.2 hours

Models: Standard System - Includes quick release buckle strap, charging rack and AC/ DC chargers

Vehicle Mount System - Includes quick release buckle strap and 12V DC vehicle-mountable direct wire charging rack

Features: IPX7 waterproof to 1m submersion

2m impact resistance tested

Articulating head aims the beam; Locking mechanism keeps head in place in "original" position

Handle clearance accommodates heavy gloves and makes hand-offs easier

Operating temperature: -20°F to 130°F. (To maintain hazardous locations rating: -20°C to 40°C)

Approvals: Class I, Division 2 Groups A, B, C, D; Class II Division 2 Groups F, G; Class III; Temperature Class T4

Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position

Meets applicable European Community Directives

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction

Description	UPC	Item #
Vulcan 180 Standard System - IEC Type C (230V) AC/12V DC, includes quick release shoulder strap - Orange - Div 2	080926-44312-9	44312
Vulcan 180 Standard System - IEC Type G (240V UK) AC/12V DC, includes quick release shoulder strap - Orange - Div 2	080926-44313-6	44313
Vulcan 180 Standard System - IEC Type I (240V AUS/NZ) AC/12V DC, includes quick release shoulder strap - Orange - Div 2	080926-44314-3	44314
Vulcan 180 Standard System - IEC Type A (120V/100V) AC/12V DC, includes quick release shoulder strap - Orange - Div 2	080926-44311-2	44311
Vulcan 180 Vehicle Mount System - 12V DC direct wire rack, includes quick release shoulder strap - Orange - Div 2	080926-44315-0	44315



#22060



#22061



#22062



#22051



#44350 Standard System Charge Rack
#44306 Direct Wire DC Charge Rack (Kit)



#45232



#44050

Description	UPC	Item #
Charging Rack AC/DC (Vulcan 180) - Black	080926-44350-1	44350
Direct Wire 12V DC Charge Kit (Vulcan 180) - Black	080926-44306-8	44306
Battery - Lithium Ion - Vulcan 180*	080926-44351-8	44351
Quick Release Strap	080926-44050-0	44050
Heavy Duty Shoulder Strap	080926-45232-9	45232
IEC Type A AC Plug (100V/120V)	080926-22060-7	22060
IEC Type C AC Plug (230V)	080926-22061-4	22061
IEC Type G AC Plug (240V)	080926-22062-1	22062
IEC Type I AC Plug (240V AUS/NZ)*	080926-22048-5	22048
DC2 direct wire charge cord*	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051

*Not shown