

microquartz

Explore our next generation microtopping in a range of modern colors and sophisticated finish.

Microquartz is a one-component high-strength decorative polymer topping system available in various colors and decorative polymer topping system available in various colors and decorative aggregates. It is fast drying and suitable for both horizontal and vertical applications.

The system is comprised of a primer (optional), aggregate body coat, and clear top coat (optional). It is applied 1/16 to 1/8 inch thick and can be finished smooth or textured for slip resistance.

Product Benefits

- Available in 15 Signature Color Blends
- Designed for interior and exterior applications
- Low VOC system (>100 g/l)
- UV resistant
- Excellent resistance to chemicals and water
- Provides a seamless joint free surface
- Meets USDA/FDA guidelines
- Provides a decorative surface resistance to slipping

Mixing Process:

Ready to use. Reactive the material for 5 minutes using a concrete mixer. Easy to apply single component formula that provides a durable, seamless, easy to maintain, slip resistant decorative surface.

Application:

1. The surface must be clean and free of any contamination. decco - The Wow Surface utilizes the International Concrete Repair Institute (ICRI) Concrete Surface Profile (CSP) standards for specifying finished surface roughness prior to applying MicroQuartz. For proper adhesion, the concrete must be a minimum #1 according to the ICRI CSP chart.

2. Prime the prepared surface with decco MicroQuartz Primer. Do not use latex bonding agents as a primer. Work the primer into the surface with a roller or soft broom or brush.

3. MicroQuartz is best applied with a trowel or squeegee. Apply as thin as possible achieving a thickness of 1/16 to 1/8 inch (12 to 15 square feet per 10 lb. of material). MicroQuartz is applied in one coat. Do not overwork the product. Troweling should be completed within 5 minutes of application.

4. For a smooth finish, trowel the surface while the material is still wet.

5. Allow the material to dry 12 to 24 hours before light traffic and 48 hours for regular traffic. Temperature and humidity will affect dry time.

6. MicroQuartz does not require a sealer, but for added protection from harsh chemicals and to aid with cleaning, MicroQuartz can be sealed with any decco water-based or high solids sealer system after the material is dry and cured. This can vary from 6 to 12 hours depending on conditions.

Clean Up:

Clean skin with soap and water. Tools and equipment should be cleaned with Xylene or Lacquer thinner. Consult MSDS for safety and health precautions.

Maintenance:

After completing the installation, the applicator should provide the owner with maintenance instructions. If floors become slippery due to animal fats, oil, grease, or soap film, clean and rinse thoroughly. Properly sealed MicroQuartz is easily cleaned with neutral soaps or detergents.

Coverage:

70 - 90 sq.ft. per pail per coat.

Presentation: 50 lbs

Shelf Life: 6 months

Warranty:

decco MicroQuartz, a proprietary product, is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective. The user assumes all other risks and liabilities resulting from use of this product. If you have any questions, please contact Bluetrade Building Materials, Inc.



decco - Miami
8217-19 NW 66th Street
Miami, FL 33166
Tel: +1 (786) 282-4097
info@heydecco.com

decco - New York
243 Grandview Ave
Staten Island, NY 10303
Tel: +1 (347) 801-2855
sales@dfstudio.nyc

www.heydecco.com
Follow us! @heydecco