

HD50

GALLERY

PRODUCT INFORMATION

HD50

Heavy Duty Cavity Wall Lintel

Cavity: 50-65mm Cavity Outer Leaf: 100mm Inner Leaf: 100mm Must have solid, fully jointed blockwork infill to inner leaf. **Features**

- Structural grade steel to EN10025
- Lack of baseplate and factory fitted insulation reduces thermal bridging
- Supergalv coating offers superior life expectancy

Length	750-180	1950-240	2550-270	2850-300	3150-360	3750-45	4650-48	4950-51
	0	0	0	0	0	00	00	00
L (kN)	70	60	60	55	50	40	35	25
W (kg/m)	14.8	14.8	17.6	17.6	17.6	17.6	17.6	17.6
H (mm)	231	231	232	232	232	232	232	232

(L) Load SWL/UDL value (W) Weight (H) Height

PRODUCT ATTRIBUTES

Brand	Birtley
Generic Ref	HD50
Product Range	Cavity Wall Lintels
Product Sub-range	50-65mm Cavity
Product Type	Heavy Duty Cavity Wall Lintel - 100mm Inner leaf/100mm Outer Leaf
European Standard/ETA	BS EN845-2:2013+A1:2016
Test Standard	EN846-9:2000/2016
Notified Body	Lucideon Ltd (NB 1289)/USWCS (NB 1679)

Material	Mild Steel S275JR to BS EN10025-2:2004
Coating/Finish/Colour	65μm Hot Dip Galvanized to BS EN ISO 1461:2009
Thermal Performance	Contact us for information
Insulation	Expanded Polystyrene - BREEAM rating A+
Fire Rating	60 mins (with 2 coat plaster finish)
1. Installation requirement	Bed fully on bricklaying mortar
2. Installation requirement	Must be used with a cavity tray - External walls only
3. Installation requirement	Must have solid, fully jointed blockwork infill to inner leaf
4. Installation requirement	150mm Minimum end bearing
Sales Qty	1
Packaging weight	0
1. Features	Supergalv coating offers superior life expectancy
1. Features 2. Features	Supergalv coating offers superior life expectancy Post-fabrication galvanizing leaves no surface with inferior paint protection
2. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection
2. Features 3. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection Lack of baseplate and factory fitted insulation reduces thermal bridging
2. Features 3. Features 4. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection Lack of baseplate and factory fitted insulation reduces thermal bridging Structural grade steel to EN10025
2. Features3. Features4. Features5. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection Lack of baseplate and factory fitted insulation reduces thermal bridging Structural grade steel to EN10025 Plaster key to inner leaf Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301