

uniarch  
Powered by Uniview Tech.

# Uniarch Brochure



## IPC Products

### StarLight Fixed Lens

#### IPC-T1E4-AF28K Network Turret Camera



- 4MP resolution
- Min. illumination:0.003Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN

#### IPC-T1E6-AF28K Network Turret Camera



- 6MP resolution
- Min. illumination:0.003Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN

#### IPC-T1E8-AF28K Network Turret Camera



- 8MP resolution
- Min. illumination:0.005Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN

#### IPC-T1E4-AF28K-B Network Turret Camera



- 4MP resolution
- Min. illumination:0.003Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB03-G-IN-BLACK, Wall mount TR-WM03-D-IN-BLACK

#### IPC-T1E6-AF28K-B Network Turret Camera



- 6MP resolution
- Min. illumination:0.003Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB03-G-IN-BLACK, Wall mount TR-WM03-D-IN-BLACK

#### IPC-T1E8-AF28K-B Network Turret Camera



- 8MP resolution
- Min. illumination:0.005Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB03-G-IN-BLACK, Wall mount TR-WM03-D-IN-BLACK

#### IPC-B1E6-AF28K Network Bullet Camera



- 6MP resolution
- Min. illumination:0.003Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 50M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB05-B-IN, Pole mount TR-UP06-C-IN

#### IPC-B1E8-AF28K Network Bullet Camera



- 8MP resolution
- Min. illumination:0.005Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 50M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67
- Optional: Junction box TR-JB05-B-IN, Pole mount TR-UP06-C-IN

#### IPC-D1E6-AF28K Network Dome Camera



- 6MP resolution
- Min. illumination:0.003Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67&IK10
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN

#### IPC-D1E8-AF28K Network Dome Camera



- 8MP resolution
- Min. illumination:0.005Lux
- Human body detection
- Powered by StarLight technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in Mic, IP67&IK10
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN



## IPC Products

### Tri-Guard Fixed Lens

#### IPC-T1P5-AF28KC Network Turret Camera



- 5MP resolution
- Min. illumination: 0.003Lux
- Smart intrusion prevention
- Powered by ColorHunter technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in mic & speaker, IP67
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN

#### IPC-T1P8-AF28KC Network Turret Camera



- 8MP resolution
- Min. illumination: 0.003Lux
- Smart intrusion prevention
- Powered by ColorHunter technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in mic & speaker, IP67
- Optional: Junction box TR-JB03-G-IN, Wall mount TR-WM03-D-IN

#### IPC-T1P5-AF28KC-B Network Turret Camera



- 5MP resolution
- Min. illumination: 0.003Lux
- Smart intrusion prevention
- Powered by ColorHunter technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in mic & speaker, IP67
- Optional: Junction box TR-JB03-G-IN-BLACK, Wall mount TR-WM03-D-IN-BLACK

#### IPC-T1P8-AF28KC-B Network Turret Camera



- 8MP resolution
- Min. illumination: 0.003Lux
- Smart intrusion prevention
- Powered by ColorHunter technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in mic & speaker, IP67
- Optional: Junction box TR-JB03-G-IN-BLACK, Wall mount TR-WM03-D-IN-BLACK

#### IPC-B1P8-AF28KC Network Bullet Camera



- 8MP resolution
- Min. illumination: 0.01Lux
- Smart intrusion prevention
- Powered by ColorHunter technology
- Fixed lens (2.8mm)
- 30M IR, 120dB WDR
- Supports 256 GB Micro SD card
- Built-in mic & speaker,
- Optional: Junction box TR-JB05-B-IN, Pole mount TR-UP06-C-IN

## NVR and Display Products

#### NVR-104E2-P4 Network Video Recorder



- 4ch NVR with 4 PoE ports
- Up to 1\*4K@30 recording
- 1 SATA HDD up to 6TB
- Bandwidth I/O: 40/40Mbps
- Support 1-ch HDMI, 1-ch VGA
- Support Ultra 265/H.265/H.264 video formats
- Support cloud upgrade

#### NVR-108E2-P8 Network Video Recorder




- 8ch NVR with 8 PoE ports
- Up to 1\*4K@30 recording
- 1 SATA HDD up to 6TB
- Bandwidth I/O: 50/40Mbps
- Support 1-ch HDMI, 1-ch VGA
- Support Ultra 265/H.265/H.264 video formats
- Support cloud upgrade

#### NVR-104X-P4 Network Video Recorder



- 4ch NVR with 4 PoE ports
- Up to 2\*4K@30 recording
- 1 SATA HDD up to 6TB
- Bandwidth I/O: 80/64Mbps
- Support 1-ch HDMI, 1-ch VGA
- Support Ultra 265/H.265/H.264 video formats
- Support cloud upgrade

#### NVR-108X-P8 Network Video Recorder



- 8ch NVR with 8 PoE ports
- Up to 2\*4K@30 recording
- 1 SATA HDD up to 6TB
- Bandwidth I/O: 80/64Mbps
- Support 1-ch HDMI, 1-ch VGA
- Support Ultra 265/H.265/H.264 video formats
- Support cloud upgrade

#### NVR-216E-P16 Network Video Recorder



- 16ch NVR with 16 PoE ports
- Up to 2\*4K@30 recording
- 2 SATA HDD up to 10TB for each HDD
- Bandwidth I/O: 160/64Mbps
- Support 1-ch HDMI, 1-ch VGA
- Support Ultra 265/H.265/H.264 video formats
- Support cloud upgrade

#### MT-22-L 22" Monitor



- True color display
- Resolution up to 1920x1080 pixels
- Wide viewing of field: 178°(H)/178°(V)
- Specific menu design, which is simple to operate
- Support 7\*24 working and lower power consumption
- Adaptively recognize signal
- VESA stand bracket
- Support multiple languages

## KIT Products

### Kit-UNA-4041W 4MP 4CH KIT WITH 4\*CAMERAS

- 1\*4ch NVR-104E2-P4
- 4\*4MP 2.8mm Fixed Lens IPC-T1E4-AF28K
- 1\*Surveillance HDD-1TB installed



### Kit-UNA-8042W 4MP 8CH KIT WITH 4\*CAMERAS

- 1\*8ch NVR-108E2-P8
- 4\*4MP 2.8mm Fixed Lens IPC-T1E4-AF28K
- 1\*Surveillance HDD-2TB installed



### Kit-UNA-4062W 6MP 4CH KIT WITH 4\*CAMERAS

- 1\*4ch NVR-104X-P4
- 4\*6MP 2.8mm Fixed Lens IPC-T1E6-AF28K
- 1\*Surveillance HDD-2TB installed



### Kit-UNA-8063W 6MP 8CH KIT WITH 4\*CAMERAS

- 1\*8ch NVR-108X-P8
- 4\*6MP 2.8mm Fixed Lens IPC-T1E6-AF28K
- 1\*Surveillance HDD-3TB installed



## PTZ Products

### IPC-P1E5-AX4PKC Network PTZ Camera

- 5MP resolution · 4X Optical Zoom
- Smart intrusion prevention
- LightHunter, 0.003Lux (F1.6)
- Built-in mic& speaker · Supports 256GB Micro SD card
- Smart IR, up to 50M IR distance
- IP66 ingress protection
- 2KV surge prevention
- Optional: Junction box TR-JB07-D-IN, Pole mount TR-UP06-C-IN



### IPC-P4P4-X25 Network PTZ Camera

- 4MP resolution · 25X Optical Zoom
- Smart intrusion prevention
- LightHunter, 0.003Lux (F1.5)
- Alarm 2 in and 1 out, Audio 1 in and 1 out
- 1 BNC video output · Supports 256GB Micro SD card
- Smart IR, up to 100M IR distance · IP67 ingress protection
- IK10 vandal resistant · 6KV surge prevention
- Optional: Wall mount TR-WE45-IN



## Switch Products

### SW-2106-P POE Switch

- 6\*100Mbps network ports (RJ45), including 4 POE/POE+ ports
- 2\*100Mbps Uplink ports
- Support standard IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
- Max capacity for single port: 30W, Total capacity: 65W
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode · All metal housing, safe and reliable



### SW-2110-P POE Switch

- 10\*100Mbps network ports (RJ45), including 8 POE/POE+ ports
- 2\*100Mbps Uplink ports
- Support standard IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
- Max capacity for single port: 30W, Total capacity: 120W
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode · All metal housing, safe and reliable





# UNIARCH BROCHURE

Powered by Uniview Tech

## StarLight Products Highlights



### StarLight

Deliver colorful image in  
the low light



### Human body detection

Reduce false alarm  
Only detect the human



### High resolution

4K resolution  
Deliver high quality image

## ColorHunter Products Highlights



### High resolution

4K products with  
high quality image



### Smart intrusion prevention


Focus on human  
vehicle and non-motor vehicle  
Reduce false alarm



### ColorHunter

Let more light in leads  
to a brighter image

## NVR Products Highlights



4K decoding  
capability,  
4K output of HDMI  
and VGA



### Smart intrusion prevention

Focus on human, vehicle  
and non-motor vehicle.  
Reduce false alarm.



### Easy to Use

Plug in & play

uniarch  
Powered by Uniview Tech.

**Life in Focus**



[www.uniarchcctv.com.au](http://www.uniarchcctv.com.au)



Sales: [sales@uniarchcctv.com.au](mailto:sales@uniarchcctv.com.au)



Technical Support: [support@uniarchcctv.com.au](mailto:support@uniarchcctv.com.au)