

# GO<sup>TM</sup>

# AUX

3" PORTABLE MONITORS



## LEGENDARY KRK SOUND QUALITY, ON THE GO

The KRK GoAux 3 portable nearfield monitors are designed to provide great sound anywhere you go. The perfect monitors for traveling musicians and engineers, they deliver renowned KRK sound quality in a mobile-friendly size. Since they're made to go wherever you do, the GoAux 3 monitors come with a convenient nylon carrying bag that holds both monitors as well as the included monitor stands and any extra cables you want to take along with you. The stands are adjustable for the optimum monitoring positioning and angle. The GoAux 3 monitors pair a 3" glass aramid woofer with a 1" soft textile dome tweeter in a 60 W RMS (total system power) bi-amplified two-way design. The rear-ported ABS cabinets are durable and supply surprising bass extension for a portable speaker. With the power amps located in one speaker's housing and the second speaker powered through an included speaker-level connection from the first, the pair only needs a single AC outlet for operation. Built-in LF and HF EQ let you adjust the monitors' response to the room and your personal preferences. Along with the 1/8" Aux and RCA stereo inputs, Bluetooth capability means you can connect wirelessly to your smartphone, computer, or other Bluetooth-capable audio devices. When you need to monitor silently, you can connect to the front panel 1/8" stereo headphone output, which automatically mutes the GoAux 3 speakers.



# GOAUX 3

## SPECIFICATIONS

<b>SYSTEM INPUTS</b>	BLUETOOTH, RCA, 1/8" AUX		
<b>SYSTEM OUTPUTS</b>	1/8" STEREO HEADPHONE JACK WITH AUTO SPEAKER MUTE		
<b>BLUETOOTH</b>	VERSION 5.0 AND OLDER COMPATIBILITY		
<b>LF TRANSDUCER</b>	3" WOVEN GLASS ARAMID		
<b>HF TRANSDUCER</b>	1" SOFT TEXTILE DOME		
<b>CROSSOVER FREQUENCY</b>	2.5 KHZ		
<b>POWER OUTPUT</b>	BI-AMPLIFIED CLASS D (60 WATTS RMS TOTAL SYSTEM POWER; 22 W RMS FOR EACH WOOFER, 8 W RMS FOR EACH TWEETER)		
<b>MAXIMUM CONTINUOUS SPL</b>	95.5 dB SPL		
<b>SYSTEM PEAK SPL</b>	99 dB SPL		
<b>MAXIMUM SYSTEM SPL, MOMENTARY PEAK</b>	105 dB SPL		
<b>FREQUENCY RESPONSE (-3 dB SPL)</b>	65 Hz - 20 kHz		
<b>FREQUENCY RANGE (-10 dB SPL)</b>	60 Hz - 22 kHz		
<b>SYSTEM DISTORTION</b>	< 0.2% THD+N 45 Hz - 20 kHz (-3 dB Max Power)		
<b>SIGNAL TO NOISE RATIO</b>	>95 dB (A-weighted) @ rated output level		
<b>COVERAGE (HORIZONTAL X VERTICAL)</b>	120 Degrees x 60 Degrees		
<b>AC INPUT VOLTAGE</b>	AC 100 - 240 V 50/60 Hz		
<b>AC POWER CONSUMPTION</b>	Idle 100/240 VAC: 5.57 W	Max Power 100/240 VAC: 60 W	Standby Mode 100/240 VAC: 0.475 W
<b>ENCLOSURE TYPE</b>	Rear Ported		
<b>ENCLOSURE MATERIAL</b>	ABS		
<b>ENCLOSURE FINISH</b>	Black Textured		
<b>DIMENSIONS (H x W x D)</b>	6.8" x 4.37" x 4.72" (172 mm x 111 mm x 120 mm)		
<b>WEIGHT</b>	6.94 lbs (3.15 kg) Including both speakers, stands, carrying bag, and included accessories		
<b>SKU</b>	GOAUX3		

