VXT GRILL INSTALLATION INSTRUCTIONS

This VXT Series Grill Kit includes the following parts:

Two (2) VXT Grills
Two (2) Rubber Gaskets
Eight (4) Face Plate Replacement Screws - Plus Four (4) Spare Screws
Eight (4) Screw Spacers - Plus Four (4) Spare Spacers
One (1) Screw Wrench

Remove the cables to your VXT monitor.

Refer to the numbered diagram on the other side of this document when following these instructions.

Find a safe, non-marring surface and gently place your VXT Cabinet 6 carefully on it's back.

IMPORTANT: Place something over the cabinet port 2 such as removable tape or tape down a piece of paper or cardboard to cover the port. If a screw or spacer piece is dropped into the port most likely it will not come out due to the port and cabinet design!

Use the included wrench and remove the four front faceplate screws on your VXT monitor.

IMPORTANT: Store these screws in a secure place as you will need them if you want to use the monitor without a grill at a later date. (The new grill screws are longer to accommodate the grill.)

Locate the mounting spacers 3. Place the mounting spacers in the indentations where you just removed the faceplate screws being careful to line up the spacers over the holes.

Take the grill 5 and carefully place it on the faceplate 4 so that the holes in the grill line up with the spacers 3 and the holes in the faceplate.

Your grills came with replacement faceplate screws 1. Locate the screws and insert them into the holes in the grill.

Tighten the screws in a criss crossing pattern a few rotations at a time until you have achieved a snug fit. Do not over tighten or the grill's shape will be deformed.

Remember to store the original screws if you want to use your monitor without the grill at a later date!





