

SAFETY DATA SHEET Permabond ET5401A

1. Identification

Product identifier

Product name Permabond ET5401A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Permabond LLC

14 Robinson Street Pottstown, PA 19464

USA

Telephone: 732-868-1372 or 800-640-7599

Website: www.permabond.com

Emergency telephone number

Emergency telephone Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport:

CHEMTREC 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200)

and is consistent with the provisions of the United Nations Globally Harmonized System of

Classification and Labeling of Chemicals (GHS).

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317

Label elements

Hazard symbols



Signal word Warning

Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Permabond ET5401A

Precautionary statements P261 Avoid breathing vapor/ spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with national regulations.

Contains EPOXY RESIN (Number average MW <= 700), TRIMETHYLOL ETHANE TRIGLYCIDYL

ETHER POLYMER, 2-PROPENOIC ACID, REACTION PRODUCT WITH

DIPENTAERYTHRITOL

3. Composition/information on ingredients

Mixtures

EPOXY RESIN (Number average MW <= 700)

60-100%

CAS number: 1675-54-3

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Not relevant.

TRIMETHYLOL ETHANE TRIGLYCIDYL ETHER POLYMER

5-10%

CAS number: 68460-21-9

REACH registration exemption - POLYMER

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Not relevant.

2-PROPENOIC ACID, REACTION PRODUCT WITH DIPENTAERYTHRITOL

5-10%

CAS number: 1384855-91-7

Classification

Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Not relevant

The full text for all hazard statements is displayed in Section 16.

Composition comments

Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Permabond ET5401A

4. First-aid measures

Description of first aid measures

Inhalation Move the exposed person to fresh air. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get

medical attention if any discomfort continues.

Skin Contact Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms

develop, obtain medical attention

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any

contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.

Most important symptoms and effects, both acute and delayed

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctorNo specific recommendations. Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Hazardous combustion

products

Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide,

and unknown hydrocarbons.

Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for

disposal.

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

7. Handling and storage

Precautions for safe handling

Permabond ET5401A

Usage precautions Avoid contact with skin, eyes and clothing. Do not breathe vapour/spray. Wash hands

thoroughly after handling. Keep container tightly sealed when not in use.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Specific end uses(s)

Specific end use(s) Adhesive.

8. Exposure controls/Personal protection

Ingredient comments WEL = Workplace Exposure Limits

Exposure controls

Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure

limits for the product or ingredients.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should

not be worn.

Other skin and body

protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility

of skin contact with this substance.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly

remove any clothing that becomes contaminated.

Respiratory protection Respiratory protection may be required if excessive airborne contamination occurs. Ensure all

respiratory protective equipment is suitable for its intended use and is NIOSH approved.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Paste.

Color White.

Odor Mild.

Odor threshold No information available.

pH Not relevant.Melting point Not available.Initial boiling point and range Not relevant.

Flash point >100°C

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

1.2 @ 23°C

Solubility(ies) Insoluble in water. Soluble in the following materials: Organic solvents.

Permabond ET5401A

Partition coefficientNot available.Auto-ignition temperatureNot applicable.

Viscosity ~350,000 cP @ 23°C Thixotropic

Not available.

Explosive properties Not relevant.

Oxidizing properties Not applicable.

Other information Not relevant.

Volatile organic compound <2 %, 20 grams/liter (Estimated)

10. Stability and reactivity

Decomposition Temperature

Reactivity The following materials may react with the product: Strong oxidizing agents. Acids.

Stability Stable at normal ambient temperatures. Polymerizes when heated.

Possibility of hazardous

reactions

Reactions with the following materials may generate heat: Amines.

Conditions to avoid Do not store near heat sources or expose to high temperatures.

Materials to avoid Amines. Strong oxidizing agents.

Hazardous decomposition

products

Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified

organic compounds.

11. Toxicological information

Information on toxicological effects

Toxicological effectsThe toxicological properties of this product have not been fully evaluated. Use of good

industrial hygiene practices is required. Avoid direct contact with skin or eyes. Do not ingest or

inhale.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitization

Skin sensitization May cause sensitisation by skin contact.

Germ cell mutagenicity

Genotoxicity - in vitro

Based on available data the classification criteria are not met.

Genotoxicity - in vivo

Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity No component of this product present at levels great than or equal to 0.1% is identified as a

known carcinogen.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Permabond ET5401A

Reproductive toxicity -

development

Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation Unlikely to be hazardous by inhalation because of the low vapor pressure of the product at

ambient temperature. In high concentrations, vapors may irritate throat and respiratory system

and cause coughing.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin Contact Irritating to skin.

Eye contact Irritating and may cause redness and pain.

Acute and chronic health

hazards

This product is moderately irritating. May cause sensitisation by skin contact.

Target Organs Eyes Skin

Toxicological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD50

11,400.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.1

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC50) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Animal data Edema score: Very slight oedema - barely perceptible (1).

Serious eye damage/irritation

Serious eye Not irritating.

damage/irritation

Respiratory sensitization

Respiratory sensitization No specific test data are available.

Skin sensitization

Permabond ET5401A

Skin sensitization Local Lymph Node Assay (LLNA) - Mouse: Sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitroConclusive data but not sufficient for classification.

Carcinogenicity

Carcinogenicity Conclusive data but not sufficient for classification.

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity -

fertility

Fertility - NOAEL 750 mg/kg/day, Oral, Rat

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: 180 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Conclusive data but not sufficient for classification.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

TRIMETHYLOL ETHANE TRIGLYCIDYL ETHER POLYMER

Acute toxicity - oral

Notes (oral LD₅₀) No specific test data are available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No specific test data are available.

Acute toxicity - inhalation

Notes (inhalation LC50) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye Causes serious eye irritation.

damage/irritation
Skin sensitization

Skin sensitization Sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitroNo specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - N

fertility

No specific test data are available.

Permabond ET5401A

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

2-PROPENOIC ACID, REACTION PRODUCT WITH DIPENTAERYTHRITOL

Acute toxicity - oral

Acute toxicity oral (LD₅o

2,000.1

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.1

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Animal data Rabbit Not irritating.

Serious eye damage/irritation

Serious eye Rabbit Irritating to eyes.

damage/irritation

Skin sensitization

Skin sensitization Local Lymph Node Assay (LLNA) - Mouse: Sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - - NOAEL 200 mg/kg, Oral, Rat F1

fertility

Reproductive toxicity - Develop

development

Developmental toxicity: - NOAEL: 10 mg/kg, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure NOAEL 75 mg/kg, Oral, Rat

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 75 mg/kg, Oral, Rat

Permabond ET5401A

Aspiration hazard

Aspiration hazard No information available.

12. Ecological information

Toxicity No data available.

Bioaccumulative potential

Partition coefficient Not available.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information Empty containers may contain product residue; follow SDS and label warnings even after they

have been emptied.

Disposal methods Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations

14. Transport information

Sea transport notes Applies only to inner containers >5 litres. See 2.10.2.7 of the IMDG code.

Air transport notes Applies only to inner containers >5 liters. See SP A197 (375)

DOT transport notes Applies only to inner containers >5 liters. See CFR 49173.155 and 172.102.173

UN Number

UN No. (International) 3082

UN proper shipping name

Proper shipping name

(International)

Environmentally hazardous substance, liquid, n.o.s. (contains Epoxy resin)

Transport hazard class(es)

Transport Labels

(International)

9

Transport labels



Packing group

Packing group (International) III

Environmental hazards

Environmentally Hazardous Substance



15. Regulatory information

Permabond ET5401A

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None above reporting levels

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None above reporting limits

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None above reporting limits

SARA 313 Emission Reporting

None above reporting limits

SARA (311/312) Hazard Categories

Acute Chronic

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

TITANIUM DIOXIDE

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US-TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None above reporting limits

16. Other information

Revision date 4/1/2020

Revision 1

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.