

# Safety Data Sheet

# **PERMABOND MT3809 A**

Revision Number: 1

Issue date: 08/03/15

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:PERMABOND MT3809 AProduct Type:Epoxy Resin

Company: PERMABOND LLC 14 Robinson Street Pottstown, PA 19464 USA Telephone: 732-868-1372 or 800-640-7599 Website: www.permabond.com

**Emergency Telephone:** 

Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport: CHEMTREC 800-424-9300

#### 2. HAZARDS IDENTIFICATION

WARNING:

CAUSES SERIOUS EYE IRRITATION CAUSES SKIN IRRITATION MAY CAUSE AN ALLERGIC SKIN REACTION

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
SKIN IRRITATION	2
SKIN SENSITIZATION	1
PICTOGRAM(S	5
Precautionary Statements	

Prevention:	Avoid breathing vapors, mist or spray. Wash thoroughly after handling. Wear protective gloves and eye protection. Contaminated work clothing must not be allowed out of the work place.
Response:	IF IN EYES: Rinse cautiously with plenty of water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Rinse with plenty of soap and water. If eye irritation occurs: Get medical attention. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.
Storage:	Not prescribed.
Disposal:	Dispose of according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	CONCENTRATION (%)*
Epoxy resin – Average MW<= 700	25068-38-6	10 – 30
(3-Glycidyloxypropyl)trimethoxysilane	2530-83-8	1 – 5

\*Exact concentration is a trade secret. Concentration ranges are provided to assist user in determining appropriate protection.

# 4. FIRST AID MEASURES Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention. Skin contact: Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms develop and persist. Eye contact: Immediately flush with large amounts of water for at least 15 minutes. Get immediate medical attention. Ingestion: Do not induce vomiting. Keep individual calm and get medical attention. Never give anything by mouth to an unconscious person. Symptoms: See section 11

#### **5. FIRE-FIGHTING MEASURES**

Extinguishing media:	Water spray or fog, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and protective clothing. In case of fire keep container cool with water spray.
Unusual fire or explosion hazards:	Keep container cool with water spray. Uncontrolled polymerization may occur at high temperature resulting in explosions or rupturing containers.
Hazardous combustion products:	Toxic and/or irritating organic vapors may be generated. Oxides of carbon.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection equipment recommended in section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent product from entering drains or waterways.
Clean-up methods:	Dyke spill to prevent from entering water ways. Ventilate area. Wear protective equipment to clean up. Soak up spill using absorbent material such as sand, silica gel, acid binder, universal binder, or saw dust. Scrape as much material as possible and store in partially filled container until disposal. Refer to section 8 (Exposure Controls/ Personal Protection) before clean up.

## 7. HANDLING AND STORAGE

 Handling:
 Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

 Keep container tightly closed.

Storage:Store in original container in a cool well ventilated area away from heat, sparks, and flames.<br/>For shelf life information contact Permabond customer service at (800)714-0170

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employees should complete an assessment of all workplaces to determine the need for and selection of proper exposure controls and protective equipment before each task is started.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epoxy resin – Average MW<= 7	00 None	None	None	None
(3-Glycidyloxypropyl)trimethoxy	silane None	None	None	None
Engineering controls:	Use local exhaust ventilation to r	maintain worker exposu	ire below established expos	ure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).			
Skin protection:	Use chemical resistant/ impermeable gloves and protective clothing to prevent skin contact.			
Eye/face protection:	Safety goggles or safety glasses with side shields.			

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Black
Odor: Odor threshold: pH: Vapor pressure:	Mild Not Available Not applicable Not applicable
Boiling point/range:	Not applicable)
Melting point/range:	Not available
Specific gravity:	1.3
Vapor density: Flash point: Flammable/Explosive limits – Lower: Flammable/Explosive limits – upper: Autoignition Temperature: Evaporation rate:	Not available >100°C (>212°F) Not available Not available Not available Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water): Decomposition temperature: VOC content:	Not available Not available <2 %, 20 grams/liter (Estimated) (for resin and hardener mixed together)

# **10. STABILITY AND REACTIVITY**

Stability:	Stable when stored under the recommended storage conditions
Hazardous reactions:	None under normal processing conditions. In the presence incompatible materials or high temperature polymerization may occur.
Hazardous decomposition products:	Oxides of carbon. Irritating organic vapors.
Incompatible materials:	Strong oxidizing agents. Strong bases. Strong acids. Amines.
Conditions to avoid:	Contact with incompatible materials which may cause polymerization. Excessive heat.

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapor or mist may cause mild respiratory track irritation.
Skin contact:	Allergic skin reaction. Skin irritation.
Eye contact:	Causes eye irritation.
Ingestion:	Not expected under normal conditions of use.

Hazardous components	LD50	LC50	Immediate and delayed Health Effects
Epoxy resin – Average MW<= 700	LD50 – Oral (RAT) 13,600 mg/Kg	None	Allergen, Irritant
(3- Glycidyloxypropyl)trimethoxysilane	LD50 – Oral (RAT) 8,030 mg/Kg LD50 – Dermal (RABBIT) 4,248 mg/Kg	None	Allergen, Irritant

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Epoxy resin – Average MW<= 700	No	No	No
(3-Glycidyloxypropyl)trimethoxysilane	No	No	No

# **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not Available

## **13. DISPOSAL CONSIDERATIONS**

#### Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State/Provincial and local governmental regulations. Refer to section 8 (Exposure Controls/Personal Protection) before handling.

#### U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Exceptions:	None

#### International Air Transportation (ICAO/IATA):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
	None

#### Water Transportation (IMO/IMDG):

**United States Regulatory Information** 

Proper shipping name:		
Hazard class or division:		
Identification number:		
Packing group:		

Not regulated None None None None

Marine pollutant:

#### **15. REGULATORY INFORMATION**

onned otates negatatory mornation	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above the reporting limits.
CERCLA/SÁRA Section 302 EHS:	None above the reporting limits.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire, Reactive
CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).
CERCLA Reportable quantity:	
California Proposition 65:	This product does not contain any chemical listed on the California Proposition 65.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Domestic Substances List.

#### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous one: New format

Issue date: 08/03/15

ADDITIONAL INFORMATION: The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guaranty of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.