Printing date 04/09/2020

Reviewed on 04/08/2020

## **1 Identification**

- · Product identifier
- · Trade name: Concrete Coat
- · Application of the substance / the mixture Protective coating
- · Uses advised against
- Processes involving extreme heat use advised against.

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving aerosol formation or vapour or dust release in excess of the assigned workplace exposure limits where workers are exposed without suitable respiratory protective equipment (RPE).

- $\cdot$  Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:** Coval Group 12705 South Kirkwood Rd., <u>100</u> Stafford, TX 77477 Tel: +1 281 566 4277 (USA) email contact: sales@coval-group.com
- Information department: Product safety department.
  Emergency telephone number: Tel: +1 281 566 4277 (USA)

## 2 Hazard(s) identification

 $\cdot$  Classification of the substance or mixture

```
GHS02 Flame
```

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Eye Irrit. 2AH319Causes serious eye irritation.STOT SE 3H336May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- Hazard-determining components of labeling: methyl acetate
- · Hazard statements

Highly flammable liquid and vapor. Causes serious eye irritation.

- May cause drowsiness or dizziness.
- · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

- Do not breathe mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Printing date 04/09/2020

Reviewed on 04/08/2020

**Trade name: Concrete Coat** 

(Contd. of page 1)

<ul> <li>Classification system:</li> <li>NFPA ratings (scale 0 - 4)</li> </ul>	(Contd. of page 1)
Health = 2 Fire = 3 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH2FIRE3REACTIVITY $\overline{0}$ Other hazards	
<ul> <li>• Results of PBT and vPvB assessment</li> <li>• PBT: Not applicable.</li> <li>• vPvB: Not applicable.</li> </ul>	
3 Composition/information on ingredients	
<ul> <li>Chemical characterization: Mixtures</li> <li>Description: Mixture of the substances listed below with nonhazardous additions.</li> <li>Dangerous components:         <ul> <li>79-20-9 methyl acetate</li> </ul> </li> </ul>	>30-≤70%
4 First-aid measures	
<ul> <li>Description of first aid measures</li> <li>General information: Immediately remove any clothing soiled by the product.</li> <li>After inhalation: Supply fresh air; consult doctor in case of complaints.</li> <li>After skin contact: <ul> <li>Immediately wash with water and soap and rinse thoroughly.</li> <li>If skin irritation continues, consult a doctor.</li> </ul> </li> <li>After eye contact: <ul> <li>DO NOT DELAY!</li> <li>Check for and remove any contact lenses.</li> <li>Rinse opened eye for several minutes under running water. Then consult a doctor.</li> </ul> </li> <li>After swallowing: <ul> <li>DO NOT DELAY!</li> <li>Wash mouth out with water</li> <li>Do not induce vomiting; immediately call for medical help.</li> <li>If vomiting occurs spontaneously, keep head below hips to prevent aspiration.</li> </ul> </li> <li>Information for doctor: Treat symptomatically and supportively.</li> <li>Most important symptoms and effects, both acute and delayed No further relevant inform</li> </ul>	nation available.
No further relevant information available.	

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

US

(Contd. of page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/09/2020

Trade name: Concrete Coat

Reviewed on 04/08/2020

• Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.

Highly flammable liquid.
Vapours form explosive mixtures with air.
Highly volatile.
Advice for firefighters
Protective equipment:
Wear self-contained respiratory protective device.
Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

## 6 Accidental release measures

Demonstrations must active active active and an encodered
• <b>Personal precautions, protective equipment and emergency procedures</b> Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Particular danger of slipping on leaked/spilled product.
Keep ignition sources away - no smoking.
· Environmental precautions:
Do not allow to enter sewers/ surface or ground water.
Do not allow to penetrate the ground/soil.
· Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
Ensure adequate ventilation.
· Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· Protective Action Criteria for Chemicals
· PAC-1:
79-20-9methyl acetate250 ppm
· PAC-2:
79-20-9methyl acetate1,700 ppm
· PAC-3:
79-20-9 methyl acetate 10000* ppm

## 7 Handling and storage

## · Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Keep away from heat and direct sunlight.

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

- Welding and other hot work operations in the work area must only be permitted under supervision.
- · Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

(Contd. on page 4)

<sup>-</sup>US-

Printing date 04/09/2020

Reviewed on 04/08/2020

**Trade name: Concrete Coat** 

(Contd. of page 3)

- $\cdot$  Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Store in a cool location. Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Store in a bunded area.
- $\cdot$  Specific end use(s) No further relevant information available.
- 8 Exposure controls/personal protection
- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

#### · Components with limit values that require monitoring at the workplace:

- 79-20-9 methyl acetate
- PEL Long-term value: 610 mg/m<sup>3</sup>, 200 ppm
- REL Short-term value: 760 mg/m<sup>3</sup>, 250 ppm
  - Long-term value: 610 mg/m<sup>3</sup>, 200 ppm
- TLV Short-term value: 757 mg/m<sup>3</sup>, 250 ppm Long-term value: 606 mg/m<sup>3</sup>, 200 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid close or long term contact with the skin.
- Do not inhale gases / fumes / aerosols.
- Do not eat or drink while working.
- Take note of assigned Workplace Exposure Limits.
- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves** 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 $(Contd. \ on \ page \ 5)$ 

US

Printing date 04/09/2020

Reviewed on 04/08/2020

(Contd. of page 4)

## **Trade name: Concrete Coat**

## · Eye protection:



Tightly sealed goggles

#### · Body protection:

Solvent resistant protective clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

Information on basic physical and cl	hemical properties
General Information	<b>F</b> - <b>F</b>
Appearance:	
Form:	Fluid
Color:	Light brown
Odor:	Solvent like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.
Flash point:	-10 °C (14 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	>250 °C (>482 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): 0.18 log POW
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	NOTE: The physical data presented above are typical values an should not be construed as a specification.

(Contd. on page 6)

Printing date 04/09/2020

**Trade name: Concrete Coat** 

Reviewed on 04/08/2020

(Contd. of page 5)

## **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- $\cdot$  Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot$  Conditions to avoid No further relevant information available.
- · Incompatible materials: Strong oxidising agents.
- · Hazardous decomposition products:
- Carbon monoxide and carbon dioxide Metal oxide

#### **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

79-20-9 methyl acetate

Oral LD50 3,705 mg/kg (rabbit)

- Primary irritant effect:
- on the skin:
- Will defat and dry the skin.

Frequent or prolonged contact may irritate and cause dermatitis.

- · on the eye: Irritating effect.
- · Subacute to chronic toxicity:

Chronic effects:: Skin damage due to contact with the liquid; high exposures might entail damage of the visual nerve.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Routes of exposure: The main route of exposure for methyl acetate is via the respiratory tract. Acute effects: Irritative effects on the eyes and the respiratory tract, disorders of the central nervous system.

#### · Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability The organic portion of the product is biodegradable.
- · Behavior in environmental systems:
- · Bioaccumulative potential Product is not expected to bioaccumulate.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Printing date 04/09/2020

Reviewed on 04/08/2020

#### Trade name: Concrete Coat

(Contd. of page 6) Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

#### · Uncleaned packagings:

#### · Recommendation:

Disposal must be made according to official regulations.

Container remains hazardous when empty. Continue to observe all precuations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

UN1231 Methyl acetate mixture 1231 METHYL ACETATE mixture METHYL ACETATE mixture
1231 METHYL ACETATE mixture
1231 METHYL ACETATE mixture
METHYL ACETATE mixture
3 Flammable liquids
3

US -

Printing date 04/09/2020

Reviewed on 04/08/2020

**Trade name: Concrete Coat** 

	(Contd. of page 7
<ul> <li>Packing group</li> <li>DOT, ADR, IMDG, IATA</li> </ul>	П
· Environmental hazards:	Not applicable.
<ul> <li>Special precautions for user</li> <li>Hazard identification number (Kemler co</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids ode): 33 F-E,S-D B
• Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1231 METHYL ACETATE MIXTURE, 3, II

## **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

#### · TSCA (Toxic Substances Control Act):

79-20-9 methyl acetate

#### · Hazardous Air Pollutants

None of the ingredients is listed.

## · Proposition 65

 $\cdot$  Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

## · Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)

Printing date 04/09/2020

Reviewed on 04/08/2020

**Trade name: Concrete Coat** 

	(Contd. of page 8
TLV (Threshold Limit Value established by A	CGIH)
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupationa	al Safety and Health)
None of the ingredients is listed.	
GHS label elements The product is classified and labeled according to Hazard pictograms GHS02, GHS07 Signal word Danger	the Globally Harmonized System (GHS).
Hazard-determining components of labeling:	
methyl acetate	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes serious eye irritation.	
May cause drowsiness or dizziness.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surface	aces No smoking.
Do not breathe mist/vapors/spray.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye pro-	
IF INHALED: Remove person to fresh air and kee	
	l minutes. Remove contact lenses, if present and easy to do
Continue rinsing.	
• Chemical safety assessment: A Chemical Safety	Assessment has not been carried out.
Other information	
This information is based on our present knowle	edge. However, this shall not constitute a guarantee for any
specific product features and shall not establish a	legally valid contractual relationship.
• Date of preparation / last revision 04/09/2020 /	_
• Abbreviations and acronyms:	
	angereuses par Route (European Agreement concerning the Internationa
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hy	gienists
EINECS: European Inventory of Existing Commercial Chemi	
ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American C	Themical Society)
NFPA: National Fire Protection Association (USA)	Litilital Society)
HMIS: Hazardous Materials Identification System (USA)	
LC50: Lethal concentration, 50 percent	
LUNU: Lathal daga NU paraant	

- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

- REL: Recommended Exposure Limit

- Flam. Liq. 2: Flammable liquids Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation Category 2A STOT SE 3: Specific target organ toxicity (single exposure) Category 3