

# XM 2/650

*forced action mixer*



## When professional want peak performance

Planetary gearing: High force transmission

2 mixing speeds for flexible use

All viscosities and types of material can be processed

The XM 2-650 forced action mixer was developed specially for high performance. Wherever high quality mixing results and high throughputs are of the essence, this is where the XM models come in.

### Technical specifications

Size of mixing bucket	17 gal.
Max. mixing volume	13 gal.
Power supply	110 volts
Mixer output	1.5 hp
Mixer rotational speed	2 x 120 / 1 x 630 rpm
Rotational speed rim scraper	37 rpm
Adjustable mixing times	90 / 180 / Duration
Weight	231 lbs
Dimensions	42.3" x 27.2" x 33,3"
Item number	39014

## **XM 2/650** *forced action mixer*



Planetary gearing



Bucket Dolly (accessory)



Rugged design

## **Faktors which make the XM such value for money**

- Short mixing cycles
- High material throughput (upt tp 1 ton/hr)
- Reproducible mixing quality means quality assurance
- All viscosities and types of material can be processed
- Powerful drive system with various speeds
- Mixing bucket changed quickly
- Durable, low-maintenance machine
- One-man operation
- Mobile
- High standard of occupational safety
- Bucket dolly (practical accessory)

### **Areas of application:**

Industrial flooring coatings • Concrete refurbishing • Screed construction  
External wall insulating systems • Color granualte flooring • ECC / PCC systems  
Synthetic resin systems • Pavement fillers • Acid-proof construction  
Sewer and water-reservoir renovation • Clay mortar • Rubber granualte for sports ground