



ENDURA CLEAN

Product Description

Power Cleaning is the first product to heal and maintain polished concrete effectively. The neutral pH of the **Power Cleaning** is ideal for removing dirt and not leaving a film. The rinse free formula safely lifts dirt without dulling the brilliance of your polished concrete floors.

Many products that are recommended for cleaning concrete are not designed for polished concrete. **Power Cleaning** is made to clean and enhance your polished concrete.

Regular use of **Power Cleaning** will increase abrasion resistance by as much as 27% over time. The chemically reactive cleaner will continue to seal and harden your concrete floors, making them easier to clean.

Power Cleaning extends the life of your polished concrete floor, reducing your maintenance cost.

Basic Applications

- Warehouses
- Manufacturing
- Schools
- Institutional Facilities
- Retail Showrooms
- Industrial Floor Slabs

Features & Benefits

- Neutral pH
- No Rinse Formula
- Compounded Concrete Hardening Chemistry
- Non Damaging
- Concentrated
- No Phosphates No Sodium Hydroxides, No Butyls
- Cost Effective

Coverage

600 to 800 sq ft/ gal in dilution

Coverage will vary due to porosity and texture of the floor

Packaging

Item Code	SKU	Gallons
CM005	938-5355	5
CM055	938-5355	55

Color

Light Blue

Shelf Life

12 months unopened

Storage Instructions

Do not break seal until product is ready for use.

Store indoors at 40°F to 100°F

Test method

Dry time

Light traffic

Heavy Traffic

Flash Point

VOC

Weight

Test results

5 min, if you use an automatic scrubber, 10 min if you use a mop and bucket

as soon as it is dry

as soon as it is dry

N/A

0 g/L

8.34 lb per gallon

Directions for Use

Prior to use, read, understand and follow all label and data page information and all safety information.

Employee education and training in safe handling of this product are recommended.

Testing: Due to the wide variety of substrates, test the product in an inconspicuous area for compatibility prior to full scale application.

New Concrete: Concrete must be fully cured prior to using an auto scrubber on the surface.

Application

Dilute 30 parts water to 1 part cleaner by volume (1 gallon of water to 4 oz of cleaner). The cleaning solution may be run through an auto scrubber or with a mop and bucket. Apply to surface allow to dwell, scrub, remove. **Power Cleaning** should not be allowed to dry on the floor as the dirt will also dry on the surface.

In cases of heavily soiled concrete **Power Cleaning** should be allowed an extended dwell time before removal. A second application may be necessary.

Limitations

Not recommended for oily surfaces.

Disposal

Dispose of according to current applicable local, state, and federal regulations.

Warranty

Legacy Chemical LLC solely and expressly warrants that for 12 months from the date of purchase its Power Cleaning products shall be free from defects in materials and workmanship, but only to the extent that the product is properly installed by applicators in accordance with its product literature and in strict compliance with the installation information and instructions in the product literature and label(s). The buyer must examine the product when received and promptly notify Legacy Chemical LLC in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If any Power Cleaning product fails to conform to this warranty, buyer's sole and exclusive remedy shall be replacement of the defective product at no cost to the buyer. Unless authorized in writing signed by an officer of Legacy Chemical LLC, no other representations or statements made by Legacy Chemical LLC or its representatives, in writing or orally, shall alter this warranty.

THE ABOVE WARRANTY AND REMEDY (i) ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES AND REMEDIES WHATSOEVER, EXPRESS OR IMPLIED, EACH OF WHICH ARE EXPRESSLY DISCLAIMED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ORDINARY OR PARTICULAR PURPOSE(S), USAGE OF TRADE AND NON-INFRINGEMENT AND (ii) SET FORTH THE ENTIRE OBLIGATION OF LEGACY CHEMICAL LLC.

LEGACY CHEMICAL LLC SHALL NOT BE SUBJECT TO AND HEREBY DISCLAIMS (EVEN IF LEGACY CHEMICAL LLC HAS BEEN ADVISED OF THE POSSIBILITY OF THE SAME): (i) ANY OBLIGATIONS OR LIABILITIES ARISING FROM BREACH OF THE ABOVE WARRANTIES, OTHER THAN THE EXCLUSIVE REMEDY EXPRESSLY SET FORTH HEREIN; (ii) ANY OBLIGATIONS OR LIABILITIES ARISING FROM TORT CLAIMS (INCLUDING, WITHOUT LIMITATION, NEGLIGENCE AND STRICT LIABILITY) OR ARISING UNDER OTHER THEORIES OF LAW WITH RESPECT TO SUCH PRODUCTS, OR ANY UNDERTAKINGS, ACTS OR OMISSIONS RELATING THERETO; AND (iii) ANY AND ALL CONSEQUENTIAL, INCIDENTAL, SPECIAL, INDIRECT, PUNITIVE, CONTINGENT, SPECULATIVE AND SIMILAR DAMAGES.

Any warranty claim must be (i) in writing and received by Legacy Chemical LLC within 60 days from the date of the claimed breach of the warranty (ii) that occurred within the 12 month warranty period. Product demonstrations, if any, are for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of such Legacy Chemical LLC products for the buyer's intended purpose(s).



Silicrete Systems

ENDURA CLEAN

14010 N STEMMONS FWY - FARMERS BRANCH, TX - 75234