

# TRU® PC SPIKED ROLLER

Specialty Finishing Roller for Self-Leveling Overlays



## PRODUCT DATASHEET

**DESCRIPTION:** The Rapid Set® TRU® PC SPIKED ROLLER is a specialty 18" (46 cm) finishing roller with included frame designed specifically for Rapid Set self-leveling products. It efficiently releases air trapped during mixing, significantly reducing pinholes. The spacing of the 2" (5.1 cm) polypropylene spikes is specially designed to maximize the aggregate exposure of TRU® PC Polished Concrete in the finished floor. The TRU PC SPIKED ROLLER also improves the uniformity of the finished floor by removing lines left by the gauge rake or smoother. The spikes are durable and can be easily cleaned for repeated use.

**USES:** Use the TRU PC SPIKED ROLLER with Rapid Set® TRU® PC Polished Concrete or any other Rapid Set® self-leveling overlayment or underlayment applied from 1/2" (1.0 cm) thick up to 1-1/2" (3.8 cm).

**ASSEMBLY:** Simply insert any standard threaded extension pole into the frame and the roller is ready for use.

**INSTRUCTIONS:** Place the self-leveling material using traditional methods. Roll the TRU PC SPIKED ROLLER in the opposite direction of the gauge rake. One pass down and back is generally all that is required to remove entrapped air. Multiple passes may be necessary if bubbles can be seen forming in the surface. Never use the TRU PC SPIKED ROLLER after the film has begun forming at the surface.

**PACKAGING:** The TRU PC SPIKED ROLLER is available in individual boxes with the frame included.

**USER RESPONSIBILITY:** Before using CTS products, read current technical data sheets, bulletins, product labels and safety data sheets at [www.CTScement.com](http://www.CTScement.com). It is the user's responsibility to review instructions and warnings for any CTS products prior to use.

**LIMITED WARRANTY:** CTS CEMENT MANUFACTURING CORP. (CTS) warrants its materials to be of good quality and, at its option, will replace or refund the purchase price of any material proven to be defective within one (1) year from date of purchase. The above remedies shall be the limit of CTS's responsibility. Except for the foregoing, all warranties expressed or implied, including merchantability and fitness for a particular purpose, are excluded. CTS shall not be liable for any consequential, incidental, or special damages arising directly or indirectly from the use of the materials.

## OVERVIEW

### Highlights:

**Durable:** Heavy duty aluminum frame with high-grade stainless steel hardware

**Minimizes Pinholes:** Efficiently releases trapped air

**Improves Floor Appearance:** Removes rake lines and assists leveling without pushing down decorative aggregate

### Manufacturer:

CTS Cement Manufacturing Corp.  
12442 Knott St.  
Garden Grove, CA 92841  
Tel: 800-929-3030 | Fax: 714-379-8270  
Web: [www.CTScement.com](http://www.CTScement.com)  
E-mail: [info@CTScement.com](mailto:info@CTScement.com)



USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.