Welch Allyn TM55 and TM65 Treadmills

Specifications

Primary Benefits:

- Ease of use The treadmill is easy to operate and whisper quiet at all speeds.
- Control The Ultradrive system is designed for smooth power and accuracy even at the slowest speeds and the heaviest weights.
- Integration TM55 and TM65 treadmills are compatible with Q-Stress® and XScribe™ stress testing systems.



The TM55 and TM65 treadmills provide a comfortable and quiet treadmill experience.

Clinicians around the world rely on our treadmills. Your patients will appreciate the solid and secure feeling the TM55 and TM65 treadmills provide, while you will appreciate how easy they are to use.

- Our easy-to-read cardiac stress systems make it simple for you to start, control and stop the treadmill.
- Clear displays let you quickly find test duration, speed and grade.
- The stress system allows you to bring your patients to a comfortable stop, gradually reducing speed and lowering the grade to zero.
- Optional rapid deceleration capability is available for the times you need to slow and stop the treadmill quickly, such as stress echo peak exercise imaging.

The Ultradrive system is the power behind the TM55 and TM65 treadmills.

Ultradrive is a digitally controlled AC-drive system that provides exceptional performance, accuracy and reliability.

- Treadmills deliver high torque for accurate speed control, even at lower speeds.
- Patients enjoy a natural walking/running sensation with no lag when the foot strikes the belt.



Welch Allyn TM55 and TM65 Treadmills **Technical Specifications** Overall: $(H \times L \times W)$ $TM55 - 46.5 \text{ in } \times 80.2 \text{ in } \times 29.9 \text{ in } (118 \text{ cm } \times 204 \text{ cm } \times 75.9 \text{ cm})$ TM65 - 46.5 in x 90.2 in x 29.9 in (118 cm x 229 cm x 75.9 cm) Running Surface: $(H \times L \times W)$ **Dimensions** $TM55 - 6.3 \text{ in } \times 55 \text{ in } \times 20 \text{ in } (16 \text{ cm } \times 140 \text{ cm } \times 51 \text{ cm})$ TM65 - 6.3 in x 65 in x 20 in (16 cm x 165 cm x 51 cm)Optional Side Handrails: (H x L) Short $-24 \text{ in } \times 40 \text{ in } (61 \text{ cm } \times 102 \text{ cm})$ Long - 44 in x 40 in (112 cm x 102 cm)Treadmill: TM55 - 352 lb (160 kg) TM65 - 375 lb (170 kg) Weight Shipping: TM55 - 500 lb (227 kg) TM65 - 525 lb (238 kg) **User Weight Capacity** 500 lb (227 kg) Speed Range 0.8 mph to 9.6 mph (1.3 km/h to 15.4 km/h) in 0.1 mph increments Incline Range 0% to 25%, in 0.5% increments Warranty 13 months parts and labor Low Voltage - 100/120 VAC @ 20 A; 50/60 Hz; NEMA 5-20R non-locking receptacle; Single-phase dedicated circuit Power $\label{eq:high-Voltage-200/230} \ \text{VAC} \ @ \ 10 \ \text{A}; \ 50/60 \ \text{Hz}; \ \text{NEMA 6-15R non-locking receptacle};$ Single-phase dedicated circuit

Specifications subject to change without notice.

For more information, contact your local Welch Allyn representative or visit www.welchallyn.com.



Clinical excellence. Connected solutions. Continuous innovation. Welch Allyn Cardiology is proud to be powered by Mortara.



