

# B-SERIES BATTERIES



## Features

Bag-like design for mounting versatility  
 Redesigned mount to fit various frame types  
 Industrial design casing to fit with the aesthetic of the CYC mid-drive product line  
 Ice-blue battery level indicators  
 Quick removal for portability  
 Fast charging capabilities  
 Weather resistant



**SCAN HERE FOR  
 QR CODE**

## General Specifications



Product	B-36	B-52	B-52	B-52L	B-52L
Rated Voltage	36V 10s2p	52V 14s2p	52V 14s2p	52V 14s3p	52V 14s3p
Capacity	10Ah (360Wh)	10Ah (520Wh)	8Ah (416wh)	15Ah (780Wh)	12Ah (624Wh)
Cell	Original Samsung 50e 21700	Original Samsung 50e 21700	Original Samsung 40T 21700	Original Samsung 50e 21700	Original Samsung 40T 21700
BMS Rating	30A continuous discharge	30A continuous discharge	70A continuous discharge	45A continuous discharge	70A continuous discharge
Max Charge Current	4 Amps	4 Amps	4 Amps	4 Amps	4 Amps

## Dimension

**B-36**



.199mm (L) X 81mm (W) X 104mm (H)

**B-52**



.259mm (L) X 81mm (W) X 104mm (H)

**B-52L**



.364mm (L) X 81mm (W) X 104mm (H)