



9599 Alpha

Manufacturing Specifications

Fiber Content:	100% EnVisionSD BCF Nylon
Dye Method:	Solution Dyed
Construction:	Loop
Pattern Repeat:	1" W x 1" L
Tufted Fiber Weight:	<u>32 oz.</u>
Gauge:	1/12
Pile Height:	.155"/.275"/.350/.458"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1.
	Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year commercial warranty.

Alpha meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9599 Alpha Color Line

00136 Volts 00237 Electrode 00335 Ionic 00638 Waves 00640 Delta 00641 Daydream 00730 Impluse 00734 Neuron 00831 Grey Matter 00832 Rhythm 00833 Pulse 00939 Theta