



9620 Censor

Manufacturing Specifications

Fiber Content:	100% EnVisionSD BCF Nylon
Dye Method:	Solution Dyed
Construction:	Loop
Pattern Repeat:	36" W x 32.50" L
Tufted Fiber Weight:	44.6oz.
Gauge:	1/10
Pile Height:	.25"/.375"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability: Flooring Radiant Panel ASTM E-648 and/or NFPA

253. Greater than 0.45 watts/CM² Class 1.

Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM

D-2859

Smoke Density: Passes NBS Smoke Chamber Test-ASTM E-662.

Colorfastness: 4.0 or better.

Static Rating: Less than 3.5 kV.

Warranty: 10 year commercial warranty.

Censor meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9620 Censor Color Line

00128 Awareness

00250 Breath

00347 Peaceful

00576 Compassion

00696 Brainwave

00742 Meditation

00779 Transformation

00782 Mindfulness

00797 Sensory

00831 Calm

00858 Visualize

00897 Immanence