



## 9598 Gamma

### Manufacturing Specifications

Fiber Content:	100% EnVisionSD BCF Nylon
Dye Method:	Solution Dyed
Construction:	Loop
Pattern Repeat:	12" W x 14" L
Tufted Fiber Weight:	32 oz.
Gauge:	1/12
Pile Height:	.155"/.275"/.350/.458"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

### PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM <sup>2</sup> Class 1.  Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year commercial warranty.

Gamma meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

## **9598 Gamma**

### **Color Line**

00136 Volts  
00237 Electrode  
00335 Ionic  
00638 Waves  
00640 Delta  
00641 Daydream  
00730 Impluse  
00734 Neuron  
00831 Grey Matter  
00832 Rhythm  
00833 Pulse  
00939 Theta