

INSPIRED BY DESIG

9699 IMAGINE

Manufacturing Specifications

| Fiber Content: | 100% EnVision® BCF Nylon |
|-----------------|--------------------------|
| Dye Method: | Solution Dyed |
| Construction: | PCU |
| Pattern Repeat: | Random |
| Ounce Weight: | 52 oz. |
| Gauge: | 1/8 |
| Pile Height: | .188 x .344 |

PERFORMANCE SPECIFICATIONS

| Flammability: | Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. |
|----------------|--|
| | Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 |
| Smoke Density: | Passes NBS Smoke Chamber Test-ASTM E-662. |
| Colorfastness: | 4.0 or better. |
| Static Rating: | Less than 3.5 kV. |
| Warranty: | 10 year wear warranty. |

Imagine meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.