



9569 Tango

Manufacturing Specifications

Fiber Content:	100% EnVisionSD BCF Nylon
Dye Method:	Solution Dyed
Construction:	Loop
Pattern Repeat:	2" W x 2" L
Tufted Fiber Weight:	32 oz.
Gauge:	1/10
Pile Height:	.093"/.156"/.250"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year commercial warranty.

Tango meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9569 Tango

Color Line

00145 Rueda
00463 Grand Plie'
00544 Chasse
00575 Aerial
00655 Jazz Hands
00696 Pirouette
00763 Arabesque
00847 Box Step
00877 Promenade
00898 Entrada