



## 9600 Zing Manufacturing Specifications

Fiber Content:	100% EnVision BCF Nylon
Dye Method:	Continuous
Construction:	Enhanced Loop
Pattern Repeat:	18" W x 28" L
Tufted Fiber Weight:	32 oz.
Gauge:	1/10
Pile Height:	.093"/.218"/.375"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

---

## PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM <sup>2</sup> Class 1.  Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year commercial warranty.

Zing meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

**9600 Zing**  
**Color Line**

00132 Sparkle  
00210 Ardor  
00313 Spirit  
00358 Vitality  
00515 Zest  
00516 Zeal  
00617 Passion  
00618 Pizzazz  
00711 Verve  
00797 Power  
00814 Mojo  
00912 Vigor