

PRODUCT SPECIFICATIONS

Contractor 3-D Full Body Harness

#7017

Features

- Dorsal and hip D-Rings for fall arrest and work positioning.
- 5-point adjustability.
- Mating buckle leg and chest.
- 1 lanyard keeper.
- Size: Universal fit.

Material Specifications

- Webbing:** *Polyester; Min. 5,000 lbs. tensile strength*
- D-Rings:** *Alloy Steel; Min. 5,000 lbs. tensile strength*
- Buckles/Adjusters:** *Alloy Steel; Min. 3,375 lbs. tensile strength*

Performance Specifications

- Tensile Strength:** *Min. 5,000 lbs.*
- Max. Capacity:** *425 lbs.*
To maintain ANSI Z359 compliance, limit total user weight to 310lbs

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *Z359.1-2007*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a Shock Absorbing Lanyard to the front or side D-Rings.



EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.

