

7021B Journeyman FLEX Aluminum

Journeyman FLEX Aluminum, Standard, Non-Belted

The Journeyman FLEX Aluminum Harness has a longstanding tradition of being the working man's harness. New design elements have been engineered into the harness for added comfort reducing fatigue to the user. With its reduced weight and added comfort, the Journeyman FLEX Aluminum harness offers unmatched durability, reliability and value.

Features

- Aluminum hardware for lighter weight
- One Dorsal D-ring
- Premium breathable padded air mesh shoulder yoke
- Quick Connect Visi-lock chest buckle
- 18" contoured leg pads
- FallTech proprietary CamLock torso adjusters
- Tongue buckle Leg Adjusters
- Non-slip dorsal D-ring adjustment
- 6" torso-sewn Waist Support Positioning Pad

MATERIALS SPECIFICATIONS

Webbing:	Polyester; Min. 5,000 lbs. tensile strength
Keepers:	Plastic
D-Rings:	Aluminum; Min. 5,000 lbs. tensile strength
Buckles/Adjusters:	Aluminum; Min. 3,375 lbs. tensile strength
Grommets:	Brass
Shoulder Adjusters:	CamLock
Foam:	High density internal foam

PERFORMANCE SPECIFICATIONS

Maximum Working Load:	425 lbs.
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

Style #	Description
PN 7021B	UniFit
PN 7021BXL	X Large
PN 7021B2X	XX Large

For shoulder and waist size ranges, please see Size Charts page.



7021B
Journeyman FLEX Aluminum

RELEVANT STANDARDS

ANSI:	Z359.11-2014
OSHA:	1926.502, 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.