

# BULLETIN

# PRODUCT SPECIFICATIONS

## 7023QC Journeyman FLEX Steel

### Journeyman FLEX Steel, Standard, Non-Belted

The Journeyman FLEX Steel continues the tradition of uncompromising performance you've come to rely on every day. New design elements have been incorporated into this jobsite workhorse for improved comfort, durability and reliability. The Journeyman FLEX Steel continues the tradition of keeping your team safe.

#### Features

- Durable alloy steel hardware
- Three D-rings; One Back and Two Hip
- Premium breathable padded air mesh shoulder yoke
- Quick Connect Visi-lock chest buckle
- 18" contoured leg pads
- Low-profile Torso Adjusters
- Quick Connect Leg Adjusters
- Non-slip dorsal D-ring adjustment

#### MATERIALS SPECIFICATIONS

<b>Webbing:</b>	Polyester; Min. 5,000 lbs. tensile strength
<b>Keepers:</b>	Plastic
<b>D-Rings:</b>	Steel; Min. 5,000 lbs. tensile strength
<b>Buckles/Adjusters:</b>	Steel; Min. 3,375 lbs. tensile strength
<b>Connectors:</b>	Steel
<b>Torsos Adjusters:</b>	Friction
<b>Foam:</b>	High density internal foam

#### PERFORMANCE SPECIFICATIONS

<b>Maximum Working Load:</b>	425 lbs.
<b>ANSI User Capacity:</b>	130 to 310 lbs. Max.
<b>OSHA User Capacity:</b>	130 to 425 lbs. Max.

#### SIZES

<b>Style #</b>	<b>Description</b>
<b>PN 7023</b>	UniFit
For shoulder and waist size ranges, please see Size Charts page.	



**7023QC**  
Journeyman FLEX Steel

#### RELEVANT STANDARDS

<b>ANSI:</b>	Z359.11-2014
<b>OSHA:</b>	1926.502, 1910.66

#### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.