

PRODUCT SPECIFICATIONS

Arc Flash 1-D Full Body Harness

7047

Features

- Dorsal D-ring for Fall Arrest with overmold insulation.
- Nomex/Kevlar blend webbing throughout
- Overmold insulation on Mating Buckle Legs, Chest and Torso adjusters
- Sizes: 7047 (UniFit), 7047XL (X-large) and 70472X (2X-Large)

Material Specifications

Webbing: Nomex®; 5,000 lbs. Min Static Strength

D-Rings: Overmolded Alloy Steel; 5,000 lbs Min

Buckles/Adjusters: Overmolded Alloy Steel; 3,375 lbs Min

ANSI Performance Specifications

Static Strength: 3,600 lbs Min

ANSI User Capacity: 310 lbs Max

OSHA User Capacity: 425 lbs Max

Relevant Standards

ANSI: Z359.11-2014

OSHA: 1926.502 and 1910.66

ASTM: F887-13

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a Shock Absorbing Lanyard to the front, side or shoulder D-Rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.