

PRODUCT SPECIFICATIONS

Deluxe Heavy-Duty Positioning Belt

#7056S

Features

- Two side d-rings for positioning.
- Removable 7-position workbelt.
- Features our stiffest, most extreme-duty workbelt.
- Reinforced waist pad.
- 8,800 lb polyester webbing.
- Size: Small

Material Specifications

Webbing:	<i>Polyester; Min. 5,000 lbs. tensile strength</i>
D-Rings:	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
Buckles/Adjusters:	<i>Alloy Steel; Min. 3,375 lbs. tensile strength</i>



Performance Specifications

Tensile Strength:	<i>Min. 5,000 lbs.</i>
Max. Capacity:	<i>425 lbs.</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>A10.32-2004, Z359.1-2007, Z359.12-2009.</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a restraint lanyard to the side d-rings.
- Never attach an SAL to a positioning belt.

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.