

PRODUCT SPECIFICATIONS

7082B3D Advanced ComforTech GEL

Standard Non-Belted Harness

All Advanced ComforTech GEL harnesses feature our exclusive polymer gel endoskeleton for unsurpassed user comfort and light weight Aluminum Alloy D-rings. Advanced ComforTech harnesses are specifically configured for Fall Arrest, Work Positioning and Climbing applications.

Features

- Premium breathable padded shoulder yoke with polymer GEL endoskeleton
- Exclusive Aluminum Alloy CamLock torso adjusters
- Proprietary Dorsal D-ring keeper with integrated SRD attachment sleeve
- Contoured removable leg pads with polymer GEL
- Forged Aluminum Alloy D-rings
- Alloy Steel Visi-lock Quick Connect chest buckle
- Alloy Steel Visi-lock Quick Connect leg adjusters
- One Dorsal and two Hip D-rings

MATERIALS SPECIFICATIONS

Webbing:	Polyester; Min. 5,000 lbs. Tensile Strength
D-Rings:	Aluminum Alloy and Alloy Steel; Min. 5,000 lbs. Tensile Strength
Buckles/Adjusters:	Aluminum Alloy and Alloy Steel; 3,375 lbs. Min Tensile Strength

PERFORMANCE SPECIFICATIONS

Static Strength:	3,600 lbs. Minimum
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES

Part #	Description
7082B3DS	Small
7082B3DM	Medium
7082B3DL	Large
7083B3DXL	X Large

For shoulder and waist size ranges, please see Size Charts page.



7082B3D

Advanced ComforTech GEL Harness

RELEVANT STANDARDS

ANSI:	Z359.11-2014
OSHA:	1926.502, 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.