PRODUCT SPECIFICATIONS

70888 FlowTech LTE

Construction Belted Harness

All FlowTech LTE harnesses feature FlowScape breathable comfort pads with air-flow ventilation for improved comfort and reduced heat and mositure buildup. Our exclusive design allows the pads to breathe when you move by pushing and pulling air in and out through the ventilation holes. Coupled with lighweight aluminum D-rings, FlowTech LTE is the lightest harnesses in its category and configured for Fall Arrest, Work Positioning and Climbing applications.

Features

- · Premium perforated shoulder yoke and waist support pads with advanced breathability
- Exclusive Aluminum Alloy CamLock torso adjusters
- · Proprietary Dorsal D-ring keeper with integrated SRD attachment sleeve
- 18" Contoured leg pads
- Forged Aluminum Alloy D-rings
- Alloy Steel Visi-lock Quick Connect chest buckle
- Extreme-Duty removable work belt with Aluminum Alloy buckle
- Alloy Steel Tongue Buckle leg adjusters
- One Dorsal and two Hip D-rings

MATERIALS SPECIFICATIONS	
Webbing:	Polyester; 5,000 lbs. Min. Tensile Strength
D-Rings:	Aluminum Alloy and Alloy Steel; 5,000 lbs. Min. Tensile Strength
Buckles/Adjusters:	Aluminum Alloy and Alloy Steel; 3,375 lbs. Min. Tensile Strength

PERFORMANCE SPECIFICATIONS

Static Strength:	3,600 lbs. Minimum
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES		
Part #	Description	
7088BS	Small	
7088BM	Medium	
7088BL	Large	
7088BXL	X Large	
7088B2X	2X Large	
7088B3X	3x Large	
For shoulder and waist size ranges, please see Size Charts page.		



7088B FlowTech LTE Harness

RELEVANT STANDARDS		
ANSI:	Z359.11-2014	
OSHA:	1926.502 and 1910.66	

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.

FALLTECH

