

PRODUCT SPECIFICATIONS

7088BR FlowTech LTE

Construction Belted Harness

All FlowTech LTE harnesses feature FlowScope breathable comfort pads with air-flow ventilation for improved comfort and reduced heat and moisture buildup. Our exclusive design allows the pads to breathe when you move by pushing and pulling air in and out through the ventilation holes. Coupled with lightweight aluminum D-rings, FlowTech LTE is the lightest harnesses in its category and configured for Fall Arrest, Work Positioning and Climbing applications.

Features

- Premium perforated shoulder yoke and waist support pads with advanced breathability
- Exclusive Aluminum Alloy CamLock torso adjusters
- Proprietary Dorsal D-ring keeper with integrated SRD attachment sleeve
- 18" Contoured leg pads
- Forged Aluminum Alloy D-rings
- Alloy Steel Visi-lock Quick Connect chest buckle
- Extreme-Duty removable work belt with Aluminum Alloy buckle
- Alloy Steel Tongue Buckle leg adjusters
- Integrated Suspension Trauma Relief System
- One Dorsal and two Hip D-rings



7088BR
FlowTech LTE Harness

MATERIALS SPECIFICATIONS	
Webbing:	Polyester; 5,000 lbs. Min. Tensile Strength
D-Rings:	Aluminum Alloy and Alloy Steel; 5,000 lbs. Min. Tensile Strength
Buckles/Adjusters:	Aluminum Alloy and Alloy Steel; 3,375 lbs. Min. Tensile Strength

PERFORMANCE SPECIFICATIONS	
Static Strength:	3,600 lbs. Minimum
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES	
Part #	Description
7088BRS	Small
7088BRM	Medium
7088BRL	Large
7088BRXL	X Large
For shoulder and waist size ranges, please see Size Charts page.	

RELEVANT STANDARDS	
ANSI:	Z359.11-2014
OSHA:	1926.502 and 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.