

PRODUCT SPECIFICATIONS

Restraint Belt with Integral Pad

#7090S

Features

- Single back d-ring for restraint.
- Fixed 7-position workbelt.
- Features our stiff and rugged heavy-duty workbelt.
- Standard waist pad.
- 8,800 lb polyester webbing.
- Size: Small

Material Specifications

- Webbing:** *Polyester; Min. 5,000 lbs. tensile strength*
- D-Rings:** *Alloy Steel; Min. 5,000 lbs. tensile strength*
- Buckles/Adjusters:** *Alloy Steel; Min. 3,375 lbs. tensile strength*

Performance Specifications

- Tensile Strength:** *Min. 5,000 lbs.*
- Max. Capacity:** *425 lbs.*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004, Z359.1-2007, Z359.12-2009.*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a restraint lanyard to the side d-rings.
- Never attach an SAL to a restraint belt.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.