

# PRODUCT SPECIFICATIONS

## 7093B FlowTech LTE

### Standard Non-Belted Harness

All FlowTech LTE harnesses feature FlowScope breathable comfort pads with air-flow ventilation for improved comfort and reduced heat and moisture buildup. Our exclusive design allows the pads to breathe when you move by pushing and pulling air in and out through the ventilation holes. Coupled with lightweight aluminum D-rings, FlowTech LTE is the lightest harnesses in its category and configured for Fall Arrest, Work Positioning and Climbing applications.

### Features

- Premium perforated shoulder yoke pad with advanced breathability
- Exclusive Aluminum Alloy CamLock torso adjusters
- Proprietary Dorsal D-ring keeper with integrated SRD attachment sleeve
- 18" Contoured leg pads
- Forged Aluminum Alloy D-rings
- Alloy Steel Visi-lock Quick Connect chest buckle
- Alloy Steel Tongue Buckle leg adjusters
- One Dorsal and two Hip D-rings



**7093B**  
FlowTech LTE Harness

### MATERIALS SPECIFICATIONS

<b>Webbing:</b>	Polyester; 5,000 lbs. Min. Tensile Strength
<b>D-Rings:</b>	Aluminum Alloy and Alloy Steel; 5,000 lbs. Min. Tensile Strength
<b>Buckles/Adjusters:</b>	Aluminum Alloy and Alloy Steel; 3,375 lbs. Min. Tensile Strength

### PERFORMANCE SPECIFICATIONS

<b>Static Strength:</b>	3,600 lbs. Minimum
<b>ANSI User Capacity:</b>	130 to 310 lbs. Max.
<b>OSHA User Capacity:</b>	130 to 425 lbs. Max.

### SIZES

Part #	Description
<b>7093BS</b>	Small
<b>7093BM</b>	Medium
<b>7093BL</b>	Large
<b>7093XL</b>	X Large

For shoulder and waist size ranges, please see Size Charts page.

### RELEVANT STANDARDS

<b>ANSI:</b>	Z359.11-2014
<b>OSHA:</b>	1926.502 and 1910.66

### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.