

PRODUCT SPECIFICATIONS

Dual-Truss Roof Anchor

#7432

Features

- Rugged steel construction, designed to mount to two adjacent trusses for superior anchor-point strength.
- For use as part of a system including two dual-truss anchors along with a FallTech 4-man temporary HLL system or with a FallTech PSR temporary HLL system for up to two users.
- Fasteners included.
- Meets the requirements of OSHA 1926 and ANSI Z359.

Material Specifications

Anchor Legs:	<i>Carbon steel, SAE 1008</i>
Cross-bar:	<i>Galvanized steel, grade 5</i>
Eye-bolt:	<i>Galvanized steel, grade 5</i>

Performance Specifications

Tensile Strength:	<i>6,500 lbs.</i>
Max. Capacity:	<i>425 lbs.</i> <i>To maintain ANSI Z359 compliance, limit total user weight to 310lbs</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>A10.32-2004, Z359.1-2007</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.