

PRODUCT SPECIFICATIONS

Permanent Roof Anchor

#7434

Features

- Permanent Roof Anchor with Stainless Steel Body
- Fastens Under Shingles, Leaving D-ring Exposed for Attachment
- 19" Including D-ring with 17" Nailing Surface
- Stainless steel strap with alloy steel d-ring.
- Rated at over 5,000 lbs..
- Meets the requirements of OSHA 1926 and ANSI Z359.

Material Specifications

Strap element: 304 stainless steel

D-Rings: Alloy Steel; Min. 5,000 lbs. tensile strength

Performance Specifications

Tensile Strength: Min. 5,000 lbs.

Max. Capacity: 425 lbs.
 To maintain ANSI Z359 compliance,
 limit total user weight to 310lbs.

Relevant Standards

OSHA: CFR1926.502, CFR1910.66

ANSI: A10.32-2004, Z359.1-2007

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.