# **PRODUCT SPECIFICATIONS**



# **Bolt-on D-ring Anchor**

#7435H

## **Material Specifications**

**D-Ring:** Alloy Steel; Min. 5,000 lbs. tensile strength

5/8" hole for user suplied fastener

**Connector Hardware:** Grade 8 fasteners recomemded

**Construction:** Forged alloy steel

### **Performance Specifications**

Tensile Strength: Min. 5,000 lbs.

Max. Capacity: 425 lbs.

To maintain ANSI Z359 compliance, limit

total user weight to 310lbs

#### **Relevant Standards**

OSHA: *CFR1926.502, CFR1910.66*ANSI: *A10.32-2004, Z359.1-2007* 

## Warnings

- · Read, understand and follow all labels and instructions prior to use.
- · Inspect before each use.
- · Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.