

PRODUCT SPECIFICATIONS

Multi-directional Temporary Toggle Anchor

#7442

Features

- Unique engineered solution designed for use in Pre-cast Concrete Structures
- 3/4" max hole diameter
- 1-1/2" min to 4" max thickness for Precast concrete and 6" min thickness for Hollowcore concrete applications
- Can be relocated and used repeatedly.
- Ideally suited for construction and maintenance applications.
- Meets the requirements of OSHA 1926 and ANSI Z359.1.

Material Specifications

Thimble:	7 x 19 wire rope with poly cover
Constituent:	7 x 19 wire rope
Wedge:	Aluminum Alloy

Performance Specifications

Tensile Strength:	<i>Min. 5,000 lbs.</i>
Max. Capacity:	<i>425 lbs.</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>A10.32-2004, Z359.1-2007</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.