

PRODUCT SPECIFICATIONS

Chain Roof Anchor

#7493A

Features

- For use on Flat or Pitched Roofs, at the ridge or field of roof
- Single person anchor point for fall arrest or restraint
- May be used in pairs as the end anchors for a 2 or 4-man Horizontal Lifeline System (HLL)
- Meets the requirements of OSHA 1926.502

Material Specifications

- Anchoring Plates:** *1/4" Carbon Steel*
- Chain:** *5/16" Grade 80 Alloy Steel Chain; Min. 5,000 lbs. tensile strength*
- O-Ring:** *2-5/16" Forged Alloy Steel ; Min. 5,000 lbs. tensile strength.*

Performance Specifications

- Tensile Strength:** *Min. 5,000 lbs.*
- Max. Capacity:** *425 lbs.*
To maintain ANSI Z359 compliance, limit user weight to 310lbs.

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.